STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

TO COMPLETE TON	_,,	
Me er Curics receives		
DISTRIBUTION	i	
SANTA FE		L
FILE		ļ
U.1.G.1.	_	
LAND OFFICE		<u> </u>
OPPRATOR	- 1	ł

OIL CONSERVATION DIVISION

Form C-103

SANTA FE	SANTA FE, NEW	36511264 10-1-10			
FILE	·		Sa. Indicate Type of Leuse		
U.S.G.S.			State Fee		
DERATOR			5. State Oli & Gas Lease No.		
			William William		
SUNDRY	NOTICES AND REPORTS ON DISALS TO DRILL ON TO OFFICE OR PLUG STORE FOR PERMIT - " (FORM C-101) FOR SU	I WELLS BACK TO A DIFFERENT RESERVOIR, C4 PROPOSALS.)			
OIL GAS	Water Injectio	n Well	7. Unit Agreement Name Cone Jalmat Yates Pool Unit		
Z. Name of Ciperator			8. Farm or Lease Name Tract 1		
J.R. Cone 3. Address of Operator			g. Well No.		
P.O. Box	10217, Lubbock, TX 79	408	10. Floid and Pool, or Wildcat		
4. Location of Well N	660 South	1980	Jalmat		
UNIT LETTER	12 22	2S 35F			
THE LINE, SECTION	13 TOWNSHIP	S 35E NM	PM. Alleria		
	15. Elevation (Show whether 3584.4 DF	er DF, RT, GR, etc.)	12. County Lea		
illillillillillillillillillillillillill		Nature of Notice, Report or	Other Data		
NOTICE OF IN		SUBSEQUE	ENT REPORT OF:		
\Box	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ABANDON	, , , , , , , , , , , , , , , , , , , ,	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT		
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB X	. —		
	[OTHER			
OTHER			The second date of starting any proposed		
17. Descrite Proposed or Completed Opwork) SEE RULE 1103.	erations (Clearly state all pertinent d	etails, and give pertinent dates, inclu	ding estimated date of starting uny proposed		
Basic well data: 285	5 feet 8 5/8 150 sx ci	rcular. 3975 feet 5 1/3	2", 900 sx cement.		
Casing perforated 3700-3862'. Completed as oil well September, 1956. Converted to water injection well July, 1963.					
injection well odly,	1505.				
Pulled 2 3/8" tubing	and packer, ran drilla	ble B.P. on 2 7/8" tubi	ng set at 3601'. Picked		
un nackon and found	leak from 927 to 951'.	Ran Ex drill, retainer	set at 800. Pumpeu		
100 sx class "c" wit	h 2% calcium chloride w bold 1500# S D - Drille	ased away S.D. Pumped dout cement tested cas	ing held 850# for 30		
minutes drilled R P	Cleaned out TD 3933'	. and laid down 2 //8"	tuping. Ran 2 3/0		
and new R-4 plastic	coated packer, set at 3	620'. Tested at 500# f	or 30 minutes.		
	•				
18. I hereby certify that the information	above is true and complete to the be	at of my knowledge and belief.			
, 10	1	Agent	7/31/85		
VICHED James A CO	YITLE_	1.3	DATE 1702100		
CHORN H			AUG - 1 1985		
APPROVED BY	TITLE_		DATE		

AUG - 1 1995

RECEIVED