NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work precified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

OTICE OF INTENTION	1 1	NOTICE OF INTENTION			INTENTION	
CHANGE PLANS		TEMPORARILY ABANDO	N WELL	TO DRILL I	DEEPER	
PLUG WELL		Notice of Intention to Plug Back		Notice of to Set Lin	Intention ver	
Squeeze		Notice of Intention to Acidize		Notice of to Shoot	INTENTION (Nitro)	
GUN PERFORATE	I	NOTICE OF INTENTION (OTHER) Salid-OI	l Frace X	Notice of (Other)	INTENTION	
IL CONSERVATION COM NTA FE, NEW MEXICO	MISSION	HIDLAND), TOXAS		APRE L 1,	1960
ntlemen :		(F	1204)		(Date)	
			The	Dani dal cita	August	
Following is a Notice of	Intention to do c	ertain work as describe	d below at the	Briwlen I	ALIEPICAL ULI	. ProdeCoe
ox 474, Midland, T	exas pany or Operator)	MERCHANT LIVE	STOCK Lesse	Well No		C (Unit)
(40-acre Subdivision)	f Sec. 14	, T, R	. 35-3 "ММРМ.	•	JALMAT	Pool
						
 Practure tre and hOO# Gyp Run tubing a 3853, 3894, 	(FOLLOW I at thru per ban. nd set brid 3906 and 39	DETAILS OF PRO NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 393 19 (Yates Sand) Derforations w	THE RULES AND F Ee -64 with 30,00 Pull tubing 8./ Perforate	egulatio 0 gals re 4 holes 9	efined oil a O degrees a	part at
 Practure tre and hOO# Gyp Run tubing a 3853, 3894, Practure tre and hOO # Gy Run tubing at 	(FOLLOW I at thru per ban. nd set brid 3906 and 39 at above 1 pban. nd retriev	NSTRUCTIONS IN 7 rods and tubing forations 3948 lge plug at 393	THE RULES AND F ge -64 with 30,00 Pull tubing 8./ Perforate). ith 30,000 gal and pull tubi /and clean out	egulatio 0 gals ra 4 holes 9 s refined	efined oil a 90 degrees a 1 oil, 75,00	part at
 Practure tre and h00# Gyp Run tubing a 3853, 3894, Fracture tre and h00 # Gy Run tubing at 	(FOLLOW I at thru per bane nd set brid 3906 and 39 at above 4 pbane nd retriev nd rods and	NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 3930 19 (Yates Sand) perforations with the bridge plug, I put well on pr	THE RULES AND F Ee -64 with 30,00 Pull tubing 8./ Perforate). ith 30,000 gal and pull tubi /and clean out roduction.	egulatio gals re holes 9 s refined ng to PBD 4	efined oil a 90 degrees a 1 oil, 75,00	part at O lbs sand
 Practure tre and 400# Gyp Run tubing a 3853, 3894, Fracture tre and 400 # Gy Run tubing a Run tubing a 	(FOLLOW I at thru per bane nd set brid 3906 and 39 at above 4 pbane nd retriev nd rods and	NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 3930 19 (Yates Sand) perforations with the bridge plug, I put well on pr	THE RULES AND I Ee -64 with 30,000 Pull tubing 8./ Perforate). ith 30,000 gal and pull tubing / and clean out roduction. THE ORITISH By	AMERICAN Company	efined oil a 90 degrees a 1 oil, 75,00 4038.	part at O lbs sand
 2. Fracture tre and 400# Gyp 3. Run tubing a 3853, 3894, 4. Fracture tre and 400 # Gy 5. Run tubing a 6. Run tubing a 6. Run tubing a 	(FOLLOW I at thru per ban. nd set brid 3906 and 39 at above 4 pban. nd retriev nd rods and	NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 3930 19 (Yates Sand) perforations with the bridge plug, I put well on pr	THE RULES AND I Ee -64 with 30,000 Pull tubing 8./ Perforate). ith 30,000 gel and pull tubi / and clean out roduction. THE CRITISH By German B. Position DIST. Com	AMERICAN Company AMERICAN	efined oil a 90 degrees a 1 oil, 75,00 4038.	part at 0 lbs sand ING COMPANY
 2. Fracture tre and 400# Gyp 3. Run tubing a 3853, 3894, 4. Fracture tre and 400 # Gy 5. Run tubing a 6. Run tubing a 6. Run tubing a 	(FOLLOW I at thru per ban. nd set brid 3906 and 39 at above 4 pban. nd retriev nd rods and	NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 3930 19 (Yates Sand) perforations with the bridge plug, I put well on pr	THE RULES AND I Ee -64 with 30,000 Pull tubing 8./ Perforate). ith 30,000 gal and pull tubing / and clean out roduction. THE CRITISH By	AMERICAN Company K	offined oil a o degrees a d oil, 75,00 038.	part at O lbs sand ING COMPANY Multo:
 2. Fracture tre and 400# Gyp 3. Run tubing a 3853, 3894. 4. Fracture tre and 400 # Gy 5. Run tubing a 6. Run tubing a 	(FOLLOW I at thru per ban. nd set brid 3906 and 39 at above 4 pban. nd retriev nd rods and	NSTRUCTIONS IN T rods and tubing forations 3948 lge plug at 3930 19 (Yates Sand) perforations with the bridge plug, I put well on pr	THE RULES AND I Ee -64 with 30,000 Pull tubing 8./ Perforate). ith 30,000 gal and pull tubi /and clean out roduction. THE CRITISH By	AMERICAN Company AMERICAN	offined oil a o degrees a d oil, 75,00 038. OIL PRODUC or opport ons regarding well Dist. Supt.	part at O lbs sand ING COMPANY Multo: