NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

TO CHANGE PLANS		TEMPORARILY ABANDON WELL	Notice of Intention to Drill Deeper	
NOTICE OF INTENTION TO PLUG WEIL	X	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention to Squeeze		Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		Notice of Intention (Other)	Notice of Intention (Other)	
OIL CONSERVATION CON Santa Fe, New Mexico	MMISSION	Hobbs, New Mexic	o June 10 (Date)	. 1963
		(Place)	(Date)	·····
Gentlemen:				
Following is a Notice of 1	Intention to do	certain work as described below at the	1e	
		Schermerhorn Stat	e _{wan bra} 1 .	P
SE 1/ SE 1/ o	pany or Operator	22 9	NMPM., Jalmat	(Unit)
(40-acre Subdivision) 74 0.	I Sec	, 1	NMPM., Jalmat	•••••••••••••••••
Propose to plug a	et at 200 and abando		/2 set at 3800.	
Propose to plug acro +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify	st at 200 and abando oss perfor oss 5 1/20 sack plug	to be left in hole; 5 1, on as follows: rations; cut 5 1/2" casin " casing stub or top said at surface with regulation	/2 set at 3800. Ig at indicated freepoint and b) at 1710; 15 sack plug acrossion marker.	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u>	st at 200 and abands oss perfor oss 5 1/2 sack plug that the	to be left in hole; 5 1, on as follows: rations; cut 5 1/2" casin " casing stub or top said at surface with regulation following offset operato	/2 set at 3800. Ig at indicated freepoint and bat 1710; 15 sack plug acrossion marker. ors have been notified as rec	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil	st at 200 and abands oss perfor oss 5 1/2 sack plug that the	to be left in hole; 5 1, on as follows: rations; cut 5,1/2" casig " casing stub or top said at surface with regulation following offset operator <u>Location of</u> NE/4 Sec. 3	/2 set at 3800. Ig at indicated freepoint and () at 1710; 15 sack plug acrossion marker. ors have been notified as red Lease 6, T225, R35E	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C	st at 200 and abands oss perfor oss 5 1/2 back plug that the bil Co.	to be left in hole; 5 1, on as follows: rations; cut 5,1/2* casin * casing stub or top said at surface with regulati following offset operator <u>Location of</u> NE/4 Sec. 3 N/2 & N/2 \$	/2 set at 3800. Is at indicated freepoint and () at 1710; 15 Sack plug acrossion marker. Ors have been notified as rec Lease 6, T225, R35E /2 Sec. 31, T225 R36E	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf 011 Corp	st at 200 and abands oss perfo- oss 5 1/2 back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5.1/2" casin casing stub or top said at surface with regulats following offset operator <u>Location of</u> NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3	/2 set at 3800. Ig at indicated freepoint and () at 1710; 15 sack plug acrossion marker. ors have been notified as rec () Lease 6, T225, R35E /2 Sec. 31, T225 R36E 6, T228, R35E	
Propose to plug a +15 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf Oil Corp	st at 200 and abands oss perfor oss 5 1/20 back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5.1/2" casin casing stub or top said at surface with regulats following offset operator <u>Location of</u> NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3	/2 set at 3800. Mg at indicated freepoint and () at 1710; 15 sack plug acrossion marker. Prs have been notified as red Lease 6, T225, R35E /2 Sec. 31, T225 R36E 6, T225, R35E Bogle Oil Company	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf Oil Corp pproved Except as follows: 25 57 Plug of 540 a	st at 200 and abands oss perfo- oss 5 1/2 back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5,1/2* casin * casing stub or top salt at surface with regulats following offset operator NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3	/2 set at 3800. Ig at indicated freepoint and () at 1710; 15 sack plug acrossion marker. ors have been notified as rec () Lease 6, T225, R35E /2 Sec. 31, T225 R36E 6, T228, R35E	
Propose to plug a +15 sack plug acro t+20 sack plug acro caming seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf Oil Corp pproved Except as follows: 25 Sy Plug of Stables 25 Sy Plug of Stables	st at 200 and abands oss perfor oss 5 1/2 back plug that the Dil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5,1/2" casin " casing stub or top said at surface with regulats following offset operato <u>Location of</u> NE/4 Sec. 3 NE/4 Sec. 3 NE/4 Sec. 3 NE/4 Sec. 3	/2 set at 3800. Ing at indicated freepoint and () at 1710; 15 Back plug across () on marker. () on marker. () at 1710; 15 Back plug across () at 1710; 15 Back plug a	
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf 011 Corp Approved Corp of Stab across from 25 SY Pluy of Stab across 25 SY Pluy of Stab across	st at 200 and abands oss perfor oss 5 1/20 Back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5,1/2* casin * casing stub or top salt at surface with regulats following offset operator NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3	/2 set at 3800. Ing at indicated freepoint and () at 1710; 15 sack plug acrossion marker. () at 1710; 15 sack plug acrossion marker. () at 1710; 15 sack plug acrossion () at 1710; 15 sack plug acrossion (puired
Propose to plug a +15 sack plug acro t+20 sack plug acro caming seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf Oil Corp pproved Except as follows: 25 Sy Plug of Stables 25 Sy Plug of Stables 25 Sy Plug of Stables	st at 200 and abands oss perfor oss 5 1/20 Back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5,1/2" casin " casing stub or top said at surface with regulats following offset operato <u>Location of</u> NE/4 Sec. 3 NE/4 Sec. 3 NE/4 Sec. 3 NE/4 Sec. 3	/2 set at 3800. Agent /2 set at 3800. Agent /2 set at 3800. /2 set at	puire d
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf 011 Corp Approved Corp of Stab across from 25 SY Pluy of Stab across 25 SY Pluy of Stab across	st at 200 and abands oss perfor oss 5 1/20 Back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5 1/2" casin " casing stub or top said at surface with regulats following offset operato <u>Location of</u> NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3 NW/4 Sec. 3	2 set at 3800. Is at indicated freepoint and at 1710; 15 Sack plug acrossion marker. Ore have been notified as rea Lease 6, T225, R35E /2 Sec. 31, T225 R36E 6, T225, R35E Bogle Oil Company Company or Operator M. J. Muit Agent Send Communications regarding well to:	puired
Propose to plug a +15 sack plug acro +20 sack plug acro casing seat; 10 a I hereby certify by Rule 201: <u>Operator</u> M. R. Antweil Continental C Gulf 011 Corp pproved xcept as follows: 25 SY Plug Strop Stab of 25 SY Plug St Yop Stab of 5 SV Plug St Yop Stab of 5 SV Plug St Yop Stab	st at 200 and abands oss perfor oss 5 1/20 Back plug that the bil Co. peration	to be left in hole; 5 1, on as follows: rations; cut 5,1/2* casin casing stub or top said at surface with regulat following offset operator <u>Location of</u> NE/4 Sec. 3 N/2 & N/2 & NW/4 Sec. 3 NW/4 Sec. 3	/2 set at 3800. Ing at indicated freepoint and () at 1710; 15 sack plug acrossion marker. () at 1710; 15 sack plug acrossion marker. () at 1710; 15 sack plug acrossion () at 1710; 15 sack plug acrossion (puire d

Continued on reverse side

Operator T. F. Hodge

, v

•00 garada U. 5. Smelting, Retining &

RW/F Sec. 36, T225, H35E W/F Sec. 36, T225, H35E SW/F SW/F Sec. 31, T225, H36E WW/L WW/E Sec. 31, T225, H36E WW/L WW/E Sec. 6, T235, H36E

^

•

. . a