

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Repr. Cag. Leak</b>	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

October 19, 1955  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the H. T. Mattern "B"  
Gulf Oil Corporation Well No. 4 in M  
(Company or Operator) (Unit)  
SW 1/4 SW 1/4 of Sec. 1, T. 22-S, R. 36-E, NMPM, Arrowhead Pool  
(40-acre Subdivision) Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to repair casing leak in 6" casing as follows:

1. Pull rods and tubing.
2. Set wire line magnesium bridge plug in base of 6" casing. Dump 2 sacks cement on top of bridge plug.
3. Run HRC tool on tubing and locate leak interval. Perforate 2 holes below bottom leak in casing and attempt to circulate with 1000# maximum.
4. Set Howco DM cement retainer on tubing above perforations in casing. Circulate cement to surface and perform bradenhead squeeze. WOC.
5. Pressure test casing. Drill out cement and retainer pressure testing at intervals. Drill out bridge plug and clean out to total depth.
6. Rerun tubing and rods. Return well to production.

Approved \_\_\_\_\_, 19\_\_\_\_  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By P. M. Linder

Title \_\_\_\_\_

Gulf Oil Corporation  
Company or Operator

By \_\_\_\_\_

Position Area Supt. of Prod.  
Send Communications regarding well to:

Name Gulf Oil Corporation

Address Box 2167, Hobbs, N. M.