NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approvai is obtained. See additional instructions in the Rules and Regulations of the Commission.

		tice by checking below:		
NOTICE OF INTENTION TO TEST CA SHUT-OFF	SING	NOTICE OF INTE	NTION TO SHO	OOT OR
NOTICE OF INTENTION TO CHANGE	PLANS	NOTICE OF INTE OTHERWISE	NTION TO PUI ALTER CASIN	LL OR
NOTICE OF INTENTION TO REPAIR V	WELL			
NOTICE OF INTENTION TO DEEPEN	WELL	NOTICE OF INTE	NTION TO PLU	JG WELL
**************************************	Hobbs, Ne	w Mexico	Aug. 10.	1940
IL CONSERVATION COMMISSION, anta Fe, New Mexico.		Place		Date
entlemen:				
ollowing is a notice of intention to do cer	rtain work as d	lescribed below at the		~===
Continental Oil Comp				
Sec. 2 7. 22-S R	36-E	N. M. P. M.,	nice	Fiel
Lea				
FULL DETA FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and cemented with 250 sag	as set in	the subject we	ll at 308	•
FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and cemented with 250 say	as set in	the subject we	ll at 308	•
FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and comented with 250 sate to set 72 hours before distributions.	as set in	the subject well-40. Cement	ell at 308	t Llowed
FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and comented with 250 sate to set 72 hours before distributed by the set 72 hours by the set 72 hours before distributed by the set 72 hours by the	as set in	the subject well-40. Cement lug.	ll at 308	t Llowed
FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and comented with 250 sate to set 72 hours before distributed by the set 72 hours by the	as set in	Continen Continen Continen Continen Continen Continen Continen Continen	tal Oil Co	llowed
FOLLOW INSTRUCTIONS IN 10 3/4" OD casing was and cemented with 250 sate to set 72 hours before di	as set in cks on 8-rilling p	Continen Contin	tal Oil Co	llowed