

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	<b>X</b>
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	<b>X</b>
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION to dually complete (OTHER)	<b>X</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

April 21, 1959  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

**Gulf Oil Corporation** (Company or Operator) **Harry Leonard (NCT-D)** Well No. **3** in **K** (Unit)  
**NE**  $\frac{1}{4}$  **SW**  $\frac{1}{4}$  of Sec. **3**, T **22-S**, R **36-E**, NMPM, **Jalmat Gas** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to drill deeper and dually complete in the South Banice Oil Pool as follows:

1. Kill well and pull tubing.
2. Drill 6-1/8" hole from 3650-3835'.
3. Run 815' of 4 1/2" OD J-55 SS casing and cement.
4. Run GR-N log with collar log. Perforate 4 1/2" liner with 4, 1/2" JHPF in selected intervals (3805-3742') and with 2, 1/2" JHPF in selected intervals (3635-3358').
5. Treat with 36,000 gallons refined oil, 1/40# Adomite per gallon and 90,000# sand in 9 equal stages. Swab and test.
6. Set Baker Model D production packer at approximately 3710'. Produce South Banice Oil thru 2-3/8" tubing and Jalmat gas thru casing-tubing annulus.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

**Gulf Oil Corporation**  
Company or Operator

By.....

Position..... **Area Production Supt.**  
Send Communications regarding well to:

Name..... **Gulf Oil Corporation**

Address..... **Box 2167, Hobbs, N. M.**