NUMBER OF COPIES RECEIVED			
DI:	TRIBUTION]
SANTA FE			7
FILE			INF
U.S.G.S.			-1142
LAND OFFICE			1
TRANSPORTER	OIL		1
	GAS		
PRORATION OFFIC			1
OPERATOR			1

W MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon Well		Notice of Intention to Drill Deeper	
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention to Plug Back		Notice of Intention to Set Liner	
		Notice of Intention to Acidize	X	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	x	Notice of Intention (Other)		Notice of Intention (Other)	X

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs, New Mexico. December 4, 1964

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Toxas. Pacific... Oil... Company......

		State	e. "A"	A/c-2		Well No.	27	inP
(Compan	or Operator)		-	Leese				(Unit)
SE	c <u>5</u>	., T2	2 S, 1	r <u> 36–</u> E ,1	NMPM.,	South	Eunic	9Pool

Lea.....County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- Disconnect well, pull rods and tubing. 1.
- 2. Run Model "D" Production Packer w/punch out plug and set at 3520" in 5-1/2" O.D. Liner.
- Run Collar Log and perforate 14 holes at selected intervals (3055-3355'). 3.
- Set Packer at 3000 & acidize perf. w/1000 gals. N.E. Frac perf. w/20,000 gals. & 20,000 # sand.
- Swab and test.
- 4. 5. 6. 7. Run tubing w/sleeve valve & seal assembly. Set blanking plug below sleeve valve & shift open sleeve valve.
- 8. Swab in gas zone, shift sleeve valve closed & pull blanking plug.
- Run rods and set lower zone to pumping. 9.
- Complete well as a gas-oil dual (gas in annulus and oil in tubing). 10.

Approved, 19, 19	Texas Pacific Oil Company Company or Operator
	Ву
Approved OIL CONSERVATION COMMISSION	PositionDistrict Engineer. Send Communications regarding well to:
By	Name Texas Pacific Oil Company
Title	Address P.O. Box 1069, Hobbs, New Mexico