



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 030132-A
Unit Closson Lease
Cities Service Oil Co.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	X
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 14, 1954

Well No. 3 is located 2310 ft. from N line and 2310 ft. from E line of sec. 6
SW SW NE 6 22 36 NMPM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Dime Lee New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 2582 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Tom Closson #3 was originally completed at a T.D. of 3630'. For the past several months, the well has been shut-in as it would produce nothing but water by swabbing. A workover unit was moved in, the hole cleaned out and P.B. to 3751' with hydromite and then perforated from 3702'-14'. (Verbal permission received from Mr. Dupont to P.B. and perforate). The well was then acidized with 1600 gallon of mud acid, this swabbed out and then reacidized with 1500 gallon. Tubing was landed at 3740 with a hookwall packer set at 3654'. Following the second acid job, 72 barrel of acid and water were swabbed from the well and it started flowing.

The well flowed 19 barrel of oil and 11 barrel of water in 5 hours on 36/64" choke. The well was then tested for 12 hours and flowed 47 barrel of oil and 40 barrel of water, GOR 9170, FTP 150%, choke 36/64".

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company

Address Box 97

Hobbs, New Mexico

By

Title Asst. Div. Supt.