


N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD



DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, by its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.


AREA 640 ACRES  
LOCATE WELL CORRECTLY

Repollo Oil Company

Hobbs, New Mexico

Company or Operator Address  
State # 157 "B" Well No. 2 in N4/4 of Sec. 7 T. 22S

R. 362 N. M. P. M. So. Dunice Field, Lea County.

Well is 1650 feet south of the North line and 350 feet west of the East line of N4/4

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced April 9, 1938 Drilling was completed May 10, 1938

Name of drilling contractor M. J. Delaney Co., Address Dallas, Texas

Elevation above sea level at top of casing 3599 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 3742 to 3823 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
15"OD	40	8		228	none				
9 5/8"	40	8		1594	Float				
7"OD	24	10		3715	Float				
2"	4.6	Reg. SSTubing		3800					

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2	15	247	250	Halliburton		
11 1/2	9 5/8	1613	400	do		
8 1/2	7"	3730	250	do		
	2" Reg.	3814 Tbg.				

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 3823 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing May 12, 1938

The production of the first 24 hours was 571 barrels of fluid of which 100 % was oil;

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

L. C. Cornett Driller A. L. Smith Driller

G. L. Rushing Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 18th Hobbs, N. Mex. May 18, 1938

day of May 1938 Name L. Surratt

Position Dist. Capt.

Representing Repollo Oil Company

Address Hobbs, N.M.

My Commission expires 2/4/42

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	238	238	Caliche, sand & Gravel
238	1320	1320	Red Rock & Red Beds
1320	137	137	Anhydrite
137	1523	1523	Salt & anhydrite
1523	71	71	Anhydrite
71	537	537	Lime