NO. OF COPIES RECEIVED					Form C-103
DISTRIBUTION					Supersedes Old
SANTA FE	NEWA	EXICO OIL CONS	SERVATION (	CURRENDA	C-102 and C-103
FILE	-				Effective 1-1-65
U.S.G.S.					Sa. Indicate Type of Lease
LAND OFFICE					State X Fee
OPERATOR	-				5. State Oil & Gas Lease No.
	U				B-1506
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PODDSALS TO BHILL OR TO DEEPEN OR FLUE BACK TO A DIFFERENT RESERVOIR. USE MAPPLICATION FOR FERMIT _** (FORM C-101) FOR SUCH PROPOSALS.)					
1.		· · · · · · · · · · · · · · · · · · ·		·····	7. Unit Agreement Nume
OIL GAS WELL X	OTHER-				
2. Name of Operator			·····	<u> </u>	8. Farm or Lease Name
Atlantic Richfield Company					State 157B
3. Address of Operator					9. Well No.
P. O. Box 1710, Hobbs, New Mexico 88240					1 1
4. Location of Well		······································			10. Field and Fool, or Wildcat
UNIT LETTER	330 FEET FRO	North	LINE AND	2310 FEET FROM	Jalmat Gas
THE LINE, SEC	TION	22S	RANGE	36E	://///////////////////////////////////
15. Elevation (Show whether D.F., RT, GR, etc.)					12. County
		<u>3603'</u> G	R		Lea
16. Check	Appropriate Boy	: To Indicate N	ature of No	tice, Report or Ot	her Data
					T REPORT OF:
				• -	
PERFORM REMEDIAL WORK	PLU	G AND ABANDON	REMEDIAL WOR	ιк []	ALTERING CASING
TEMPORARILY ABANDON			COMMENCE DR	ILLING OPNS.	PLUG AND ABANDONMENT X
PULL OR ALTER CASING	CHA	NGE PLANS	CASING TEST A	ND CEMENT JAB	
			OTHER		
OTHER		[]			
12 Describe Describe Constraints					
<ol> <li>Work) SEE RULE 1103.</li> </ol>	perations (Clearly sta	te all pertinent deta	uls, and give p	ertinent dates, including	s estimated date of starting any proposed

Rigged up to plug and abandon on 12/3/75. Killed well and installed BOP. POH w/completion assy. Ran 2-3/8" OD EUE tbg OE to 3650' & spotted 10 sx c1 c cmt (35') on top of BP @3685'. Filled hole w/heavy gelled mud between all cmt plugs. Spotted 40 sx cl c cmt across Jalmat perfs 3430-3638'. Cmt went into Jalmat perfs. POH w/tbg. Ran 7" CIBP on WL & set @3380'. Ran 2-3/8 EUE tbg to 3375', spotted 10 sx cl c cmt (35') on top of plug. Top of plug @ 3345'. Spotted 20 sx cl c cmt (100' plug) across top of salt @1712'. Top of plug @1612'. Spotted 10 sx cmt plug @ surface. Installed regulation dry hole marker, cleaned & levelled location. Well P&A eff: 12/06/75.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Zn

NS OF APPROVAL, IF ANY:

Dist. Drilling Supervisor

December 8, 1975