

F ORD OF DRILL-STEM AND SPECIAL TES

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3840' feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing April 23, 19 38

OIL WELL: The production during the first 24 hours was 1080 barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 31

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 1465'	T. Devonian	T. Ojo Alamo
T. Salt. 2095'	T. Silurian	T. Kirtland-Fruitland
B. Salt. 3090'	T. Montoya	T. Farmington
T. Yates. 3230'	T. Simpson	T. Pictured Cliffs
T. 7 Rivers. 3455'	T. McKee	T. Menefee
T. Queen. 3830'	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash.	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn.
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	175	175	Sand				
175	195	20	Red rock				
195	1465	1270	Red bed & shells				
1465	1572	107	Anhydrite				
1572	1627	55	Red rock, salt & Anhydrite				
1627	2095	468	Anhydrite & salt				
2095	3090	995	Salt & anhydrite				
3090	3105	15	Anhydrite				
3105	3115	10	Lime				
3115	3154	39	Lime & Anhydrite				
3154	3244	90	Lime				
3244	3310	66	Broken Lime				
3310	3448	138	Lime				
3448	3475	27	Broken Lime				
3475	3615	140	Lime				
3615	3635	20	Broken Lime				
3635	3780	145	Lime				
3780	3840	60	Broken lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 15, 1954

(Date)

Company or Operator Texas Pacific Coal and Oil Co.

Address Box 1688 Hobbs, New Mexico

Name John Yuruka

Position or Title District Engineer

Santa Fe, New Mexico

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Texas Pacific Coal and Oil Company
(Company or Operator)

N.M. State "A" A/c 2
(Lease)

Well No. 10, in SW 1/4 of SW 1/4, of Sec. 8, T. 22-S, R. 96-E, NMPM.

South Eunice Pool, Lea County.

Well is 660' feet from South line and 330' feet from West line

of Section 8 If State Land the Oil and Gas Lease No. is A-983

Drilling Commenced March 20, 1938 Drilling was Completed April 21, 1938

Name of Drilling Contractor..... **George P. Livermore**

Address.....Lubbock, Texas

Elevation above sea level at Top of Tubing Head.....**3610'**..... The information given is to be kept confidential until
....., 19.....

OIL SANDS OR ZONES

No. 1, from 3710' to 3840' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
12 1/2"	50#	New	167'				
9 5/8"	36#	New	3144'				
7"	24#	New	3700'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17"	12 1/2"	177'	200			
12"	9 5/8"	315 1/4'	250			
8 3/4"	7"	3710'	200			

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.....

.....**Depth Cleaned Out**.....