

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Texas Pacific Coal and Oil Company, P. O. Box 2110, Ft. Worth, Texas

Company or Operator
State "A" Ac.2, Well No. 26 in NE 1/4 of Sec. 8, T. 22-S
Lease R. 36-E N. M. P. M. So. Eunice Field, Lea County.

Well is 660 feet south of the North line and 1980 feet west of the East line of Section 8

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced February 19, 1943 Drilling was completed March 13, 1943

Name of drilling contractor T. P. C. & O. Co. Address

Elevation above sea level at top of casing 3588 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3365 to 3419 No. 4, from 3755 to 3800
No. 2, from 3511 to 3543 No. 5, from to
No. 3, from 3719 to 3725 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
10"	40			524'					
7"OD	24			3702'					
3"	-			3872' (RUE tubing)					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	10"	524	200			
	7"OD	3702	250			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	2,000	3-15-43		
		"	3,000	3-16-43		
		By KKK Chemical Process Co.				

Results of shooting or chemical treatment Initial production 168 bbls.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3890 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing March 15, 1943
The production of the first 24 hours was 168 barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

J. R. Teague, Supt., Texas Pacific Coal and Oil Co. Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records, to the best of my knowledge & belief.

Subscribed and sworn to before me this 22nd

day of March, 1943

L. A. Hartung Notary Public

My Commission expires 6-1-43

Fort Worth, Texas March 22, 1943

Name

Position Agent

Representing TEXAS PACIFIC COAL AND OIL COMPANY
Company or Operator

Address

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	50	50	Caliche
50	90	40	Sand, Gravel, Shells
90	245	155	Shale, Shells
245	390	145	Red Bed, Shells
390	458	68	Red Bed
458	643	185	Red Bed, Shells
643	926	283	Shale, Red Rock
926	1333	407	Red Bed
1333	1455	122	Shale, Anhy., Shells
1455	1505	50	Anhydrite
1505	1794	289	Salt, Anhy.
1794	2011	217	Salt, Anhy., Shells
2011	2287	276	Salt, Anhy, Shells
2287	2548	260	Salt
2548	2780	232	Salt, Anhy.
2780	2956	176	Salt, Anhy, Shells
2956	3009	53	Anhy., Shells
3009	3029	20	Anhydrite
3029	3157	128	Anhydrite, Lime
3157	3179	22	Lime
3179	3221	42	Broken Anhy. & Lime
3221	3292	71	Lime, Anhydrite
3292	3365	73	Lime
3365	3385	20	Lime, Oil, Gas, Sand
3385	3410	25	Lime, Oil, Gas show
3410	3511	101	Lime
3511	3543	32	Lime, Oil Gas
3543	3719	149	Lime
3719	3725	6	Lime, Oil, Gas
3725	3755	30	Lime
3755	3800	45	Lime, Oil, Gas
3800	3880	80	Lime
3880	3890	16	Lime, Oil, Gas

Total Depth 3890'