

Orig: & cc: OCC  
cc: FHR  
JTR  
F

(Form C-103)  
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) Acid & Sand Free	<input checked="" type="checkbox"/>

April 13, 1955  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company  
(Company or Operator)

State #157 2A  
(Lease)

Oscar Borg Drilling Company  
(Contractor)

Well No. 2 in the NW 1/4 SE 1/4 of Sec 9

T. 22 S., R. 36 E., NMPM., South Emilee Pool, Lea County.

The Dates of this work were as follows: April 5, 8, 10, 11, 1955

Notice of intention to do the work (X) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD - 3850 - set 7" OD casing @ 3849 and cemented with 300 sacks cement. Ran temperature survey which indicated top of cement back of 7" casing @ 2520 from surface. Let cement set 72 hours and tested pipe with 1,000# pump pressure for 30 minutes before and after drilling plug. No decrease in pressure. Drilled cement plug to 3848. Ran Electric logs. FBTD 3848 - Perforated 7" casing w/4 jet shots per foot from 3712-44, 3749-55, 3759-74. Swabbed dry, acidized w/1,000 gallons of 15% mud acid @ 1700# @ 1.9 bbl per minute. Swabbed & recovered lead oil, Sand Fraced w/6,000 gallons of oil and 6,000# of sand @ 4600#, @ 5.5 barrels per minute. Swabbed & recovered lead oil. Flowed 166 barrels new oil in 11 hours. Last 6 hours @ 15 barrels per hour.

Witnessed by H. A. Lund  
(Name)

Sinclair Oil & Gas Company  
(Company)

Foreman  
(Title)

Approved: OIL CONSERVATION COMMISSION

*S. G. Stanley*  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name *CC. Saiter*

Position Dist. Supt.

Representing Sinclair Oil & Gas Company

Address 520 East Broadway, Hobbs, New Mexico

1. The first part of the document is a list of names and addresses of the members of the committee.

2. The second part is a list of the names of the members of the committee.

3. The third part is a list of the names of the members of the committee.

4. The fourth part is a list of the names of the members of the committee.

5. The fifth part is a list of the names of the members of the committee.

6. The sixth part is a list of the names of the members of the committee.

7. The seventh part is a list of the names of the members of the committee.

8. The eighth part is a list of the names of the members of the committee.

9. The ninth part is a list of the names of the members of the committee.

10. The tenth part is a list of the names of the members of the committee.