



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico 000

1958 MAY 11 AM 9:11
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

SINCLAIR OIL AND GAS COMPANY
(Company or Operator)

STATE 157 "A"
(Lease)

Well No. 3, in SE 1/4 of SE 1/4, of Sec. 9, T. 22S, R. 36E, NMPM.
South Dixie Pool, Lea County.

Well is 660 feet from South line and 660 feet from East line
of Section 9. If State Land the Oil and Gas Lease No. is 2-1506

Drilling Commenced April 26, 1958 Drilling was Completed May 5, 1958

Name of Drilling Contractor Sabre Drilling Company

Address Midland, Texas

Elevation above sea level at Top of Tubing Head 3540' The information given is to be kept confidential until
, 19.

OIL SANDS OR ZONES

No. 1, from 3740' to 3845' No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	22.74	N	330				Surface
5-1/2"	17 & 15.5	N	3050			3750'-3782'	Production
2-3/8"	4.7	N	3735				Tubing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4"	8-5/8"	330	250	Halliburton		
7-7/8"	5-1/2"	3050	200	"		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand-Oil Fractured with 20,000 gallons refined oil and 20,000# sand thru perforations
from 3750' - 3782'.

Result of Production Stimulation Well flowed 294 bbls. oil in 24 hours.

Orig. & Acc: 000 - Nabha
cc: State Land Office
cc: FRB, NPD, File

Depth Cleaned Out

CORD OF DRILL-STEM AND SPECIAL TE

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 3850' feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing May 11, 19 58

OIL WELL: The production during the first 24 hours was 294 barrels of liquid of which 100 % was
was oil; 0 % was emulsion; 0 % water; and 0 % was sediment. A.P.I.
Gravity 34.5

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
liquid Hydrocarbon. Shut in Pressure _____ lbs.

Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy. 1275'
T. Salt. 1486'
B. Salt. _____
T. Yates. 2586'
T. 7 Rivers. 3076'
T. Queen. 3482'
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Drinkard _____
T. Tubbs _____
T. Abo _____
T. Penn _____
T. Miss _____

Northwestern New Mexico

T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Farmington _____
T. Pictured Cliffs _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Dakota _____
T. Morrison _____
T. Penn _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1275	1275	Sand & Red Beds				
1275	1486	211	Red beds and anhydrite				
1486	2586	1100	Salt and Anhydrite				
2586	3076	490	Lime and anhydrite				
3076	3482	406	Lime and Dolomite				
3482	3633	151	Lime and Shell				
3633	3850	217	Lime, Dolomite and Sand				
			T. D. - 3850'				
			PSYD - 3845'				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

May 12, 1958
(Date)

Company or Operator Sinclair Oil & Gas Company

Address 520 E. Broadway, Hobbs, New Mexico

Name C. G. Salter

Position or Title District Superintendent