

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

TEXAS PACIFIC COAL AND OIL COMPANY

P. O. Box 2110, Fort Worth 1, Texas

Company or Operator

Address

State New Mexico "A" Ac. 2 Well No. 30 in NW 1/4 of Sec. 9, T. 22-S

Lease

R. 36-E, N. M. P. M., So. Dunice Field, Lea County.

Well is 1980 feet south of the North line and 660 feet west of the East line of Section 9

If State land the oil and gas lease is No. 2A Assignment No. A-983

If patented land the owner is _____, Address _____

If Government land the permittee is _____, Address _____

The Lessee is _____, Address _____

Drilling commenced September 19, 1945 Drilling was completed October 27, 1945

Name of drilling contractor M. B. K. Drilling Co., Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3563 feet.

The information given is to be kept confidential until _____ 19____.

OIL SANDS OR ZONES

No. 1, from 3710' to 3840' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	40			307'					
7-5/8	26.40			1548					
5-1/2	14			3700					
2	4.7			3820					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	10"	307'	225			
	7-5/8	1548	200			
	5-1/2	3700	200			
	2	3820	-			

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	3000	10-28-45	3710-3840'	

Results of shooting or chemical treatment Flowed

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3840 feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing _____ 19____

The production of the first 24 hours was 114 barrels of fluid of which 100 % was oil; _____ %

emulsion; _____ % water; and _____ % sediment. Gravity, Be _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

M. B. K. Company Driller _____, Driller _____, Driller _____

_____, Driller _____, Driller _____

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9th

Fort Worth, Texas November 9, 1945

day of November, 1945

Name E. SchaperPosition Agent

L. A. Hartung Tarrant County, Texas

Representing TEXAS PACIFIC COAL AND OIL COMPANY

Company or Operator

My Commission expires 6-1-47

Address _____

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	240	240	Clay & Caliche
240	270	30	Caliche & Rock
270	315	45	Red Shale
315	1248	933	Red Bed
1248	1295	47	Shale
1295	1380	85	Red Bed & Shells
1380	1420	40	Red Bed & Red Rock
1420	1490	70	Red Rock
1490	1505	15	Red Bed, Anhydrite & Shells
1505	1612	107	Anhydrite
1612	1700	88	Anhydrite ; Salt
1700	1775	75	Anhydrite, Salt, Shells
1775	2830	1055	Anhydrite & Salt
2830	2870	40	Sand & Salt
2870	2960	90	Anhydrite
2960	2978	18	Gyp
2978	3015	37	Anhydrite & Gyp
3015	3040	25	Anhydrite & Lime
3040	3125	85	Lime
3125	3153	28	Lime ; Gyp
3153	3165	12	Lime
3165	3306	141	Lime & Gyp
3306	3312	6	Lime & Chert
3312	3840	528	Lime

TOTAL DEPTH ----- 3840'