## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we. or tories accrives		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.	T	
LAND OFFICE		
OPERATOR	$\top$	

## DIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 Revised 10-1-

FILE SANTA FE, N	EW MEXICO 87501		
U.S.G.S.		5a. Indicate Type of Lease	
LAND OFFICE		State XX Fee.	
OPERATOR		5. State Oil & Gas Lease No.	
		······································	
SUNDRY NOTICES AND REPORTS  OF HOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DECEPTE OR PL  USE "SPECIATION FOR PROMIT -" (FORM C-101) FOR	ON WELLS  UG BACK TO A DIFFERENT RESERVOIR.  SUCH PROPOSALS.		
I.  OIL GAB OTHER.		7. Unit Agreement Name	
2. Name of Operator ·		8. Farm or Lease Name	
Sun Exploration & Production Co.		State "A" A/C 2	
P. 0. Box 1861 Midland, TX 79702		9. Well No.	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER L 1980 FEET FROM THE SOUTH	LINE AND 660 FEET FROM	South Eunice 7 Rivers	
THE West LINE, SECTION 9 TOWNSHIP	22-SHANGE 36-E HMPM.		
15. Elevation (Show when	her DF, RT, GR, etc.)	12 County	
16.		Lea MIIIII	
Check Appropriate Box To Indicat NOTICE OF INTENTION TO:		er Data REPORT OF:	
PERFORM REMEDIAL WORK	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT	
PULL OR ALTER CABING CHANGE PLANS	CASING TEST AND CEMENT JOB	_	
: -	OTHER Re-entry to prop	erly P & A T	
N3MT0	_		
17. Describe Proposed or Completed Operations (Clearly state all pertinent	details, and give pertinent dates, including	estimuted date of starting any propose	
work) SEE RULE 1103.			
8-28 Bled 8-5/8 - 5-1/2 csg Ann from 170			
8-29 Weld on 5-1/2 collar, NV WH & BOP/R Fell thru had strong gas blow, died	<pre>IH 3-7/8" bit on 1-3-1/8 DC immediately/lwr bit to 67'</pre>	/tagged & drld cmt 5-31 /POH/RIH w/2-3/8 W.S. O.	
to 378' tagged up.		•	
8-30 RIH w/3-7/8" bit, 2-3-1/8 DC's on 2-3/8 W.S. to 378' Drilled wood & paper 378-381,			
Fell thru/lwr bit to 3385. Drilled hard cmt 3385-3388/circ hole clean/POH/RIH			
w/2-3/8 O.E. to 3357 8-31 Circ hole w/9.0 ppg MUD/POH/CAFFEE shot 5-1/2 collar @ 1212' w/nitro charge/POH			
& rec 39 jts 5-1/2 csg/top of 5-1/2 stub @ 1212/RIH 2-3/8 tbg 0.E. to 1260/McCaffee			
spot 50 sx class "C" plug 1260-1090		0.1. 10 1200/11cgarree	
9-1 RIH w/2-3/8 WS, tag cmt plug @ 1039		erf 4 sqz hole 930-931.	
RIH 2/AD-1 pkr on 2-3/8 WS, set pkr	@ 63', press 8-5/8 csg to	1000 for 30 min., releas	
pkr & POH, Caffey perf 4 sqz holes	400-401', RIH w/AD-1 pke on	2-3/8 WS, set pke @ 252	
Est inj rate 3 BPM @ 400 pse, circ 400-252.	out Braden head, pump 200 s	xs cmt plug from	
9-2 Press test cmt plug to 500 psi for	5 min OK, released pkr & PO	H, RIH w/2-3/8 WS, open	
end to 252', spot 40 sxs cmt plug 2	52 to 116', POH lay down 2-	3/8 WS, spot 10 sxs cmt	
surface plug, cut well off 4' below	unu-level, weld on steel p	iale, install marker.	
18. I hereby certify that the information above is true and complete to the be	at of my knowledge and belief.	فديد يو	
	<b>A</b>		
*16.10 Dethan temp TITLE_	Associate Accountant	9-4-84	
in in the second		17.8 14.0	
CONDITIONS OF APPROVAL IN ANY	OH COACHRONICA CAR	DATE A ASSES	
mg ar maria	THE OF LEASE CHARACTER AND AND A PARKET	The same of the sa	

RECEIVED
SEP 5 1984