



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

R. Olsen Oil Co. Denver, Col., New Mexico.
Company or Operator Address
James Well No. 1 in Corral of Sec. 10 T. 22S
Lease
R. 30S N. M. P. M. South Dunice Field, Lea County.
Well is 1900 feet south of the North line and 1900 feet west of the East line of of 10 Sec. 10
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Hattie Jones Address Dunice, New Mex.
If Government land the permittee is Address
The Lessee is Address
Drilling commenced 3/11 19 49 Drilling was completed 3/29 19 49
Name of drilling contractor Beebe and Olsen Address Jal, New Mexico.
Elevation above sea level at top of casing feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3100 to 3405 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13 3/8		8		310	Howco				Surface
7	80	8		3128	Howco				Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/4"	13 3/8"	310	200	Howco		
8 3/4"	7"	3128	750	Howco	10.7	

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3405 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 3/29/49 19 (waiting on pipeline connection.)
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours 9000 MCF Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. 1535

EMPLOYEES

C.C. Beebe Driller J.D. White Driller
J.D. White Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this Jal, New Mexico 3/30/49.
day of 19 Name R. Olsen Oil Co. Date
 Position
 Representing R. Olsen Oil Co.
 Company or Operator
 Address
My Commission expires

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	15	15	Caliche
15	190	175	Shale red
190	215	25	Sand (water)
215	1790	1575	Shale red sandy
1875			
1790	1900	110	Anhydrite (Russler)
1900	3130	1230	Salt, Anhydrite and shale
3130	3495 TD	315	Sand and sandy dolomite (Fates 3130)