

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

JUL 31 1939

HOBBS OFFICE

WELL RECORD

DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Texas Pacific Coal & Oil Company, P.O. Box 2110 Fort Worth, Texas

Company or Operator

Address

State New Mex. "A" Ac. 2 Well No. 17 in NE¹/₄ of Sec. 11, T. 22-S

Lease

R. 36-E N. M. P. M. So. Eunice Field, Lea County.

Well is 2310 feet south of the North line and 330 feet west of the East line of Sec. 11.

If State land the oil and gas lease is No. N.M.2-A Assignment No. A-983

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced June 13, 1939 19 Drilling was completed July 4, 1939 19

Name of drilling contractor Address

Elevation above sea level at top of casing 3513 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3718- to 3790 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10-3/4 7"OD	40# 24#	373		373 3665				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	10-3/4 7	373 3665	175 400	Halliburton "		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3790 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing July 6, 1939

The production of the first 24 hours was 720 barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

T.E. Massey, Sept. Texas Pacific Coal and Oil Co. Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records, to the best of my knowledge & belief.

Subscribed and sworn to before me this

Fort Worth, Texas July 27, 1939

day of 27th July, 1939

Name

Position

Representing TEXAS PACIFIC COAL & OIL COMPANY

Company or Operator

My Commission expires 6-1-41

Fort Worth, Texas

0	35	35	Caliche
35	145	110	Sand
145	312	67	Rock, Sand & Red Bed
312	418	106	Red Bed & Rock
418	600	182	Rock, Sand & Red Bed
600	604	4	Sand rock
604	722	118	Rock, Sand & Red Bed
722	1295	573	Rock & Red Bed
1295	1357	63	Red Bed
1357	1490	133	Broken Anhy.
1490	1525	35	Red Bed & Shells
1525	1535	10	Shale & shells
1535	1568	33	Rock & Red Bed
1568	1570	2	Red bed shells
1570	1628	58	Salt, shells, broken
1628	1728	100	Anhy. & salt
1728	1842	114	Salt, Shells broken
1842	2250	408	Anhy. salt
2250	2300	50	Potash
2300	2315	15	Gyp
2315	2408	93	Anhy. shells-Salt
2408	2493	85	Salt shells
2493	2615	122	Salt & Anhydrite
2615	2625	10	Anhydrite and lime
2625	2690	65	Anhy, Gyp. & lime shells
2690	2702	12	Lime
2702	2969	267	Anhy. & Lime
2969	3012	43	Anhy., Lime, strk shale
3012	3036	24	Sdy. lime & anhy.
3036	3071	35	Lime
3071	3106	35	Anhy. & lime
3106	3170	64	Lime
3170	3202	32	Anhy. & lime
3202	3260	58	Lime
3260	3323	63	Lime & Anhy.
3323	3353	30	lime
3353	3415	62	Lime & anhy.
3415	3501	86	Lime
3501	3515	14	Lime-strks gas sand
3515	3562	47	Lime
3562	3580	18	Lime
3580	3585	5	Lime, Brkn.
3585	3612	27	Lime
3612	3626	14	Lime
3626	3790	164	Lime

Total Depth 3790'