

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
157	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Plug & abandon		7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
Atlantic Richfield Company		State 157 "D"	
3. Address of Operator		9. Well No.	
P. O. Box 1710, Hobbs, New Mexico 88240		3	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER J, 2310 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 12 TOWNSHIP 22S RANGE 36E NMPM.		Arrowhead Grayburg	
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3174' DF		Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐



ALTERING CASING ☐

PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Rigged up on 11/10/75, installed BOP & POH w/completion assy. WIH w/7" cmt retr on tbgr & set retr @ 3556'. Squeezed 50 sx Cl C cmt cont'g 4% gel & 8# salt/sk thru retr. Stung out of retr & spotted 7 sx (35') on top of cmt retr. Spotted heavy gelled mud between all cmt plugs. Ran free point on 7" csg, indicated free @ 772'. Cut csg @ 760', attempted to pull. Could not pull. Cut csg @ 680' & pulled, rec 650'. Spotted 55 sx Cl C cmt cont'g 4% gel & 8# salt/sk, (100' cmt plug) across 7" OD csg stub & top of salt. Spotted 55 sx Cl C cmt across 10-3/4" OD csg shoe @ 332'. Spotted 10 sx cmt @ surface, installed regulation dry hole marker, cleaned & leveled location. P&A eff 11/17/75.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	TITLE Dist. Drlg. Supv.	DATE 11/19/75
APPROVED BY 	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		