


N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

The Ohio Oil Company Box 1607, Hobbs, New Mexico
Company or Operator Address
State McDonald 17 in SENE of Sec. 13, T. 22 South
Lease Well No. in of Sec. T. South
R. 36 East, N. M. P. M. South Eunice Field, Lea County.
Well is 1650 feet south of the North line and 330 feet west of the East line of Section 13-22-36
If State land the oil and gas lease is No. A-2614 Assignment No. _____
If patented land the owner is _____, Address _____
If Government land the permittee is _____, Address _____
The Lessee is _____, Address _____
Drilling commenced April 3 19 40 Drilling was completed April 20 19 40
Name of drilling contractor Noble Drilling Corp., Address Tulsa, Oklahoma
Elevation above sea level at top of casing 3461 feet.
The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from 3707 to 3750 Pay No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
<u>9-5/8</u>	<u>32#</u>	<u>None</u>		<u>334'</u>	<u>Regular</u>			
<u>4-1/2</u>	<u>9#</u>	<u>8</u>		<u>3627</u>	<u>Float</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>10"</u>	<u>8-5/8</u>	<u>334</u>	<u>125</u>	<u>Halliburton</u>		
<u>6-3/4"</u>	<u>4 1/2"</u>	<u>3627</u>	<u>300</u>	<u>Halliburton</u>		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3760 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing May 1 19 40
The production of the first 24 hours was 131 barrels of fluid of which 100 % was oil; 0 % emulsion; 0 % water; and 0 % sediment. Gravity, Be 35
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

S. N. Poteet Driller Red Davis Driller
M. J. Winters Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 1stday of May 19 40

Notary Public

My Commission expires March 2, 1941Hobbs, New Mexico 5-1-40Name D. L. ProvincePosition ForemanRepresenting The Ohio Oil CompanyAddress Box 1607, Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	162	162	Caliche & Sand
162	650	488	Red Beds
650	925	275	Red Beds and Red Rock
925	1150	225	Red Rock
1150	1255	105	Anhydrite
1255	1275	20	Salt
1275	1618	343	Salt and Anhydrite
1618	1980	362	Salt & Anhydrite & Shells
1980	2355	375	Salt & Anhydrite
2355	2403	48	Anhydrite
2403	2448	45	Broken Anhydrite
2448	2514	66	Anhydrite
2514	2718	204	Anhydrite & Gypsum
2718	2821	103	Anhydrite & Lime
2821	2870	49	Anhydrite & Gypsum & Broken Lime
2870	2906	36	Anhydrite & Lime
2906	2957	51	Anhydrite
2957	3100	43	Anhydrite & Lime
3100	3148	48	Anhydrite & Gypsum & Lime
3148	3193	45	Broken Lime
3193	3236	43	Lime and Anhydrite
3236	3760 (TD)	524	Lime