

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

The Ohio Oil Company Hobbs, New Mexico
Company or Operator Address
State McDonald a/o 2 Well No. 22 in NW/4, SE/4 of Sec. 13, T. 22-S
Lease R. 36-E Arrowhead Lea County.
N. M. P. M. Field, Lea
Well is 2970 feet south of the North line and 1650 feet west of the East line of Sec. 13-22-37
If State land the oil and gas lease is No. A-2614 Assignment No.
If patented land the owner is, Address
If Government land the permittee is, Address
The Lessee is The Ohio Oil Company Address Hobbs, New Mexico
Drilling commenced August 13, 1948 Drilling was completed August 28, 1948
Name of drilling contractor Oil Well Remedial Service Address Odessa, Texas
Elevation above sea level at top of casing 3465 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3756 to 3781 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
	NO CHANGE IN CASING RECORD								
Tbg. 2-3/8"	4.7#	8 rd.	Smls.	3789'			3763	3781	
							3768	3765	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
		re-set				
2-3/8	tbg.	3778'				

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	1000 gal.	8/22/48	3763 - 3781	

Results of shooting or chemical treatment Well pumping 30 B/O in 24 hrs., 48 bbls. water

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from 3756 feet to 3781 feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing September 1, 1948
The production of the first 24 hours was 30 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be. 33 @ 60
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Bill Birdwall Driller M. P. Groves Driller
Russell Swage Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30

day of September 1948

Notary Public

My Commission Expires August 10, 1951

My Commission expires

Hobbs, New Mexico 9/30/48

Name J. P. Groves

Position Superintendent

Representing The Ohio Oil Company

Company or Operator

Address Box 1607, Hobbs, New Mexico

