

NO.	COPIES RECEIVED		
	DISTRIBUTION		
OFFICE			
FOR			

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.		
A-2614		

## SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Atlantic Richfield Company

3. Address of Operator

P. O. Box 1710, Hobbs, New Mexico 88240

4. Location of Well

UNIT LETTER L, 660 FEET FROM THE West LINE AND 1980 FEET FROM  
THE South LINE, SECTION 14 TOWNSHIP 22S RANGE 36E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

McDonald WN State

9. Well No.

1

10. Field and Pool, or Wildcat

Jalmat Gas

15. Elevation (Show whether DF, RT, GR, etc.)

3532' GR

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 3/5/75 rigged up and plugged & abandoned in the following manner: Spotted 100 sx Cl C cmt cont'g 4% gel and 8#/sk salt, btm plug @ 3390'. POH w/tbg. RIH w/tbg & checked TOC @ 3332'. Set tbg @ 3330' & spotted 100 sx Cl C cmt cont'g 3#/sk salt. POH w/tbg. WIH w/tbg & tagged TOC @ 2441'. Filled hole w/9# mud. POH w/tbg. No free point indicated on 8-5/8" csg. WIH w/tbg to 1600', spotted 100 sx Cl C, 4% gel, 8# salt from 1300-1600' in 8-5/8" casing. Perf'd 13-3/8" csg @ 300' w/6 shots (2 JSPF). WIH w/cmt retr on 2-7/8" tbg. Set retr @ 250'. Cmt'd 8-5/8" X 13-3/8" annulus w/120 sx Cl C 2% CaCl. MP 700#. Pmpd 20 sx on top of retr. POH w/tbg. Spotted 10 sk cmt plug @ surface. Installed regulation dry hole marker. P&A effective 3/11/75.

Your office to be notified when location is ready for final inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge.

SIGNED H. J. Bernard

TITLE Dist. Drlg. Supv.

DATE 3/13/75

APPROVED BY John W. Rumpson

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 1 1976

OIL CONSERVATION COM.  
WASH., D. C.