NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST NOTICE OF INTENTION TO TEST WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in triplicate.

You are hereby notified that we intend to test the shut-off of water in State McDon Well No 3 in NV1 SE1 of Sec. 16 , T. 22 , R. 36 N. M. P. M., South Eunice on 4-25 19 35 . 13 3/8 in 48 lb. casing was formation at a depth of 287 feet on 19 23. Cemented XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	
State Geologist, Santa Fe, New Mexico. Dear Sir: You are hereby notified that we intend to test the shut-off of water in State McDon Well No 3 in W SE of Sec. 16 , T. 22 , R. 36 N. M. P. M., South Eunice Oil Field Lea on 4-25 19 35 13 3/8 in 48 lb. casing was cemented formation at a depth of 287 feet on Eay 23. 200 sacks of Oil Well cement was as follows: Halliburton Fluid level will be bailed to a depth of Bottom feet and left undisturbed for	
Well No 3 in NW SET of Sec. 16 , T. 22 , R. 36 N. M. P. M., South Eurice on 4-25 19 35 . 13 3/8 in 48 lb. casing was formation at a depth of 287 feet on 19 23, 200 sacks of 011 Well cement was as follows: Halliburton	
Well No 3 in NW SE of Sec. 16 , T. 22 , R. 36 N. M. P. M., South Eurice	
N. M. P. M., South Eurice Oil Field Cemented South Eurice Oil Field Commented South Eurice Oil Field Commented South Eurice In Red In	ald
formation at a depth of 287 feet on 23. The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of 30 feet and left undisturbed for	
formation at a depth of 287 feet on 23, 200 sacks of Cil Well cement w The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of Bottom feet and left undisturbed for	
The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of Bottom feet and left undisturbed for	Beds
The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of Bottom feet and left undisturbed for	19 35
The method used in placing the cement was as follows: Halliburton Fluid level will be bailed to a depth of Bottom feet and left undisturbed for	ere used.
Additional information:	
Approved 4-24 1935 Sincerely yours,	
Except as follows: The Ohio Oil Company or Oil Com	perator.
By Illule Polish	
Position Supt.	
Send communication regarding well	to
Name The Chic Oil Company	
Address P. O. Box 00, Hobbs, N	ew Mexico

a Police (1871), i som tronomick skytomick (1871), i som tronomick skytomick (1871), i som tronomick skytomick All Mario (1884), i som tronomick skytomick skytomick skytomick (1884), i som tronomick skytomick skytomick sky

- TANDAN A TANDAN A

	and the state of t		
	<i>€</i>		
			id (
			grafia Programa
	* * * * * * * * * * * * * * * * * * *		
	· ·		•
			:
$\frac{d^2}{dt} = \frac{1}{2} \left(\frac{1}{2} \frac{dt}{dt} + \frac{1}{2} \frac{dt}{dt} \right)$	4 4 .	54 - 1 ₅	
to the state of th	1.5.	*:	, .
			4 -
	green was b		
	me to the		
	7.5	· · · · · · · · · · · · · · · · · · ·	1 g
$\frac{1}{2} \frac{d^2 x}{dx^2} = \frac{1}{2} 1$	$\mathbf{x}_{i}^{(t)}$		81 For # 1 124
	into a tiga a Turkan		
. 7.			