

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

THE OHIO OIL COMPANY, P. O. BOX 1607, HOBBS, NEW MEXICO.

Company or Operator **STATE McDONALD** Well No. **9** in **NW 1/4 SW 1/4** of Sec. **16**, T. **22 S.**, R. **36 E.** N. M. P. M. **EUNICE** Field, **LEA** County.
Well is **1980** feet south of the North line and **660** feet west of the East line of **Sec. 16**.
If State land the oil and gas lease is No. **A-2514** Assignment No. _____
If patented land the owner is _____, Address _____
If Government land the permittee is _____, Address _____
The Lessee is _____, Address _____
Drilling commenced **9/18/37** 19____. Drilling was completed **10/15** 19____
Name of drilling contractor **Oil Well Drlg. Co.**, Address **Hobbs, New Mexico.**
Elevation above sea level at top of casing **3556** feet.
The information given is to be kept confidential until _____ 19____.

OIL SANDS OR ZONES

No. 1, from **3775** to **3856** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	40#			206	Reg.			
9-5/8"	36			1513	Float			
7"	24			3662	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2"	13"	206	200	Halliburton	10	40
11	9-5/8"	1513	500	"	"	"
8-3/4"	7"	3662	300	"	"	"

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	3,000 gal.	10-14		

Results of shooting or chemical treatment **75 barrels of oil per hour**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3856** feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **Oct. 16** 19**37**
The production of the first 24 hours was **75** barrels of fluid of which **100** % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be. _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Jack Randolph, Driller **O. E. Gill**, Driller
Raymond C. Cosby, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **18th** day of **October**, 19**37** Hobbs, N.M. **Oct. 18, 1937**
Name **[Signature]**

FORMATION RECORD

801-1-12

FROM	TO	THICKNESS IN FEET	FORMATION
0	180	180	Surface Sand
180	210	30	Red Bed
210	370	160	Red Beds
370	795	425	Red Rock & sand
795	1083	288	Red Rock & Sand
1083	1170	87	Red Rock & shells
1170	1280	110	Red Rock & Gyp&shells
1280	1314	34	Red Rock, Gyp & shells
1314	1426	112	Red Rock & shells
1426	1468	42	Red Rock & shale
1468	1493	25	Anhydrite
1493	1590	97	Anhydrite
1590	1665	75	Anhydrite & salt
1665	1807	142	Anhydrite & salt
1807	1945	52	Anhydrite, shale & streaks of salt
1945	2445	500	Salt, Anhydrite & shale
2445	2640	195	Salt, Anhydrite & potash
2640	2685	45	Salt & potash
2685	2715	30	Gyp & Anhydrite
2715	2900	185	Salt & Anhydrite
2900	3050	150	Anhydrite & Gyp
3050	3060	10	Anhydrite & lime
3060	3115	55	Anhydrite, gyp & lime
3115	3152	37	Anhydrite & lime shells
3152	3238	86	Anhydrite & lime
3238	3244	6	Lime, slight gas
3244	3256	12	Lime
3256	3536	280	Lime
3536	3604	68	Broken lime, showing gas.
3604	3680	76	Lime
3680	3856	176	Lime