

COPY

(SUBMIT IN TRIPLICATE)

Land Office Las CrucesLease No. 030132-BWell No. Closson-3UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

JUN 13 1951

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 20, 1950

Well No. 5 is located 560 ft. from N/S line and 1980 ft. from E/W line of sec. 18NW 1/4 Sec. 18
(1/4 Sec. and Sec. No.)22S
(Twp.)36E
(Range)NMPN
(Meridian)South-Eunice
(Field)Lea
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 3607 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

It is recommended that Well No. 5 on the Closson-3 lease (No. 030132-B), be plugged and abandoned.

This well was originally completed in the Seven Rivers producing horizon at a total depth of 3316' in November, 1950. After going dead from water encroachment and artificial lift methods failed to produce any oil or gas the well was plugged back and casing perforated in several attempts to recomplete the well as a gas well, but all attempts failed and well was finally PB 3350' with cement and temporarily abandoned.

It is now proposed that the 5 1/2" casing be cut off at as low a point as it can be found free in the hole and the free casing pulled. The hole will then be completely loaded with heavy mud & a cement plug be spotted at the point the casing is cut off and the open hole cemented back to 1520' on the base of the 8-5/8" casing. The 8-5/8" csg. will then be tested to determine if there is any free casing and if so the free csg. will be reclaimed and the open hole cemented to the surface. If there is no free 8-5/8" csg. the top 100' of 8-5/8" csg. will be cemented inside. Cont'd on page 2:

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil CompanyAddress Drawer 7, Hobbs, New MexicoBy /s/ L. A. ElyTitle District Superintendent