


Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 030132-b

Unit Closson B

Cities Service Oil Company

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	X
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	X
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 31, 1958

Well No. 9 is located 1990 ft. from ~~SW~~ [S] line and 1960 ft. from ~~SW~~ [E] line of sec 19-22-36

NWSE 19 22-S 36-E NNFH
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Jalmat Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3556 ft (D.F.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Moved in workover rig at Closson B Well #9 2-4-58. Killed well, pulled inner tree and installed BOP. Pulled 2" thg. Ran 131 jts. of 2 7/8" drill pipe w/4 3/4" bit, junk basket, and reamer. Cleaned out to T.D. 3556'. Drilled and cored to 3808'. Reamed hole to 3773'. Ran guard log, GR-N, Caliper log, plugged back w/3 sax reg. neat cement from 3808' to 3773'. Ran 4 1/2" Hydril Liner (12 jts.) broke thru bridge plug at 3773', set liner @ 3808'. Cemented w/40 sax latex cement. Lost circ., attempted to squeeze liner w/50 sax, tool set @ 3376', cement would not squeeze, waited 6 hrs. to attempt squeeze w/100 sax cement. Max. press. 1200#, would not squeeze. Reset tool at 3316', pumped into formation @ 600#, pumped 50 sax cement w/25% floccs w/2 bbls. in formation, pressured up to 2000#, dropped to 200# in 20 min. pull thg. WOC 18 hrs. Drilled cement & cleaned out to 3800'. Perforated 3720 to 3766' (46') w/4 jets/ft. 184 holes-

(continued on Page -2-)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Cities Service Oil Company

Address Box 97

Hobbs, New Mexico

By [Signature]

Title Dist. Supt.

