

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 25, 1952

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Service Oil Company

(Company or Operator)

Closson "B"

(Lease)

Ralph Johnson Oil Company

(Contractor)

Well No. 6 in the SW 1/4 NW 1/4 of Sec. 20

T 22 S, R. 36 E, NMPM, South Eunice Pool, Lea County.

The Dates of this work were as follows: June 16, 1952 through June 21, 1952

Notice of intention to do the work (was) ~~for record~~ submitted on Form C-102 on June 9, 1952

(Cross out incorrect words)

and approval of the proposed plan (was) ~~for record~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The Cities Service Oil Company's Closson "B" No. 6 well has been recompleted as a gas well as follows: Surface head and equipment was removed and tubing pulled and well logged with Lane wells to a depth of 3512'. Tubing was then rerun with a Halliburton retainer on bottom, retainer set at 3493' and open perforations from 3514' to 3534' squeezed with 200 sack of cement in two stages of 100 sack each. A squeeze was tested with 3000# pressure and held without pressure drop.

Tubing was then pulled and the 5 1/2" casing gun perforated with 20 1/2" holes from 3450' to 3470'. Tubing was then rerun and well swabbed in to natural flow. After cleaning well up it was tested for 24 hrs. on 30/64" choke and flowed 1,435 M.C.F. of gas and 8 barrel of water with 220# flowing tubing pressure.

Witnessed by W. J. Ely Cities Service Oil Company Dist. Superintendent

(Name)

(Company)

(Title)

Approved:

OIL CONSERVATION COMMISSION

Ray Guthrie

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name W. J. ElyPosition District SuperintendentRepresenting Cities Service Oil CompanyAddress Box 97, Hobbs, New Mexico

(Title)

(Date)