

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

MOBBS OFFICE O. C. C.
JUN 22 8 39 AM '64

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	Remedial

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Dallas, Texas
(Place)

6-18-64
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Dalport Oil Corporation - A. L. Christmas "D"
(Company or Operator)

Well No. **1** in **0**
(Unit)

SW $\frac{1}{4}$ **SE** $\frac{1}{4}$ of Sec. **21**, T. **22S**, R. **36E**, NMPM., **South Eunice Oil** Pool
(40-acre Subdivision)

Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull pump, rods & tubing
2. Run tracer survey & cement bond log to check if old perfs. from 3712-3815 should be retreat.
3. Run retrievable bridge plug and packer on tubing to isolate zones between 3712-3815 (ed to be acidized. Acidize 300 gallons spearhead. Pull tubing, packer & bridge plug.
4. Run cardinal Rubber Sleeve to seal off part of old perfs.
5. Frac old perfs. down casing with 20,000 gal. control frac plus 20,000# sand with ball seal-
6. Perforate with single entry 3614, 3620, 3627, 3637, 3665, 3673, 3687 and 3693. Set (ers retrievable bridge plug with tubing at 3700.
7. Spot 250 gallons Spearhead on perfs. Inject 500 gallons acid, 10,000 gallons control frac + 10,000# sand.
8. Pull retrievable bridge plug. Cleanout to TD
9. Place well back on production

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

DAIPOINT OIL CORPORATION

By.....
Company or Operator

Position.....
Send Communications regarding well to:

Name.....
Address.....**930 Fidelity Union Life Bldg. Dallas, Texas**

