

1980' FSL & 1980' FW
 Sec 21, T-22S, R-36E
 Elev: 3534' 6L; 0'-8.

Completion History:

- 2-5-38: Completed TD: 3842'
- 3-20-54: P13: 3635'
- Per F 3140'-3560'
- Acid w/3000 gals
- Frac w/6000 gals oil + 1^{1/2} gal sd
- 12-12-56: CO-3832'. PB-3811'
- Frac w/5000 gals oil + 1^{1/2} gal sd
- 12-21-56: Frac 3140'-3560' w/20,000 gals + 1^{1/2} gal sd
- 11-1-70: SI oil zone
- 8-23-73: CO-3811'. 6 IH w/2^{1/4}" rbg to produce gas. Convert OH to Injection
- 9-3-73: SI injection
- 6-9-74: Squeeze 35 SA @ shoe 3695'
- Squeeze 3140'-3560' w/300 SA
- CO-3818', Install PC rbg
- 8-16-84: CO-3811'. Acid w/500 gals
- 11-13-85: CO-3811'
- 7-30-87: SI. Thg leak

13^{3/8}" 27.8"
 @ 36' w/60 SA
 (Circ)

8^{5/8}" 32"
 @ 1362' w/600 SA
 (Circ)

TOC @ 2600'

117 jts 2^{3/8}" plastic coated tbg w/6" Baker AD-1 pkr @ 3650'

- * 3140'-46'
 - * 3146'-3220'
 - * 3240'-3380'
 - * 3420'-3560'
- Squeezed w/300 SA

3670'-80' w/4 JSPE
 6", 16" @ 3695' w/150 SA

5^{1/2}" OH

PBTD: 3811'

TD: 3842'

Made By JDL
 Checked By
 Date 10-7-87
 Page of

Conoco Inc.
 Calculation Sheet

Title South Eunice Unit No 18
 Proposed

Job No.
 Field Nm FV
 State NM