NE MEXICO OIL CONSERVATION COMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indi	icate natui						
NOTICE OF INTENTION TO TEST CASING	SHUT-OFF	X	NOTICE C CHEMI	F INTENT CALLY TRI	ON TO SEAT WELD	HOOT OR	
NOTICE OF INTENTION TO CHANGE PLANS			NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING				
NOTICE OF INTENTION TO REPAIR WE	LL		NOTICE O	F INTENTIO	ON TO PL	UG WELL	
NOTICE OF INTENTION TO DEEPEN WE	ELL						
Ke	ermit.	Texas		1/	22/37		
			Place			Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:							
Following is a notice of intentiton to do				it the	- <u>-</u>		
Company or Operator	Lease		er	Well No		in	M 7
of Sec. 21 T. 225	R. 361	<u>\$</u> , N.	М. Р. М.,_	Eunic	36		Field,
Los	County.	• • •					
FULL DI FOLLOW INSTRUCTI 9 5/8" 36# ST S Depth of hole,1545", and test easing by building 30 minutes before and a at 12 e'elock AM.	SS Cas: 1d. com 3 up pi	ing set ented wi	at 1542 th 450 to 1200	*6" in sacks	Anhyd sement allow	rite. . We w to set	ill for
9 5/8" 36# 8T S Depth of hole, 1545, and test easing by building 30 minutes before and s	SS Cas: 1d. com 3 up pi	ing set ented wi	at 1542 th 450 to 1200	*6" in sacks	Anhyd sement allow	rite. . We w to set	ill for
9 5/8" 36# 8T S Depth of hole, 1545, and test easing by building 30 minutes before and s	SS Cas:	ing set ented wi	at 1542 th 450 to 1200 g plug.	# 6" in sagks (# and) Test w	Anhyd sement allow ill be	rite. • We w to set made	ill for
9 5/8" 36# ST S Depth of hole,1545 ar test easing by building 30 minutes before and at 12 e'elock AM.	S Cas:	ing set ented wi	at 1542 th 450 to 1200	tinent	Anhyd sement allow lll be	rite We wante made	ill for
9 5/8" 36# ST S Depth of hole,1843", and test easing by building 30 minutes before and at 12 e'elock AM.	S Cas:	ing set ented wi ressure irilling	at 1542 th 450 to 1200 g plug.	tinent	Anhyd sement allow ill be	rite We wante made	ill for
9 5/8" 36# ST S Depth of hole, 1545° ar test easing by building 30 minutes before and at 12 e'clock AM. Approved_ except as follows:	S Cas:	ing set ented wi ressure irilling	at 1542 th 450 to 1200 g plug.	tinent	Anhyd sement allow lil be Pet. Company o	corp.	ill for
9 5/8" 36# ST S Depth of hole,1545 ar test easing by building 30 minutes before and at 12 e'elock AM.	S Cas:	ing set ented wi ressure irilling	at 1542 th 450 to 1200 g plug. Nid-Con By // a	tinent	Anhyd ement allow lil be Company o	Corp.	ill for 1/24/37
9 5/8" 36# 8T S Depth of hole, 1545° at test easing by building 30 minutes before and at 12 e'clock AM. Approved except as follows:	SS Cas: ad come y up pr after 6	ing set ented wi ressure lrilling	at 1542 th 450 to 1200 g plug. Nid-Con By // a	tinent wed	Pet. Company of the restrictions in the restriction in the	Corp.	ill for 1/24/37
9 5/8" 36# 8T S Depth of hole, 1545° and test easing by building 50 minutes before and at 12 e'clock AM. Approved— except as follows:	SS Cas: ad come y up pr after 6	ing set ented wi ressure lrilling	at 1542 th 450 to 1200 g plug. By Aa Position B	tinent tinent tinent commun	Pet. Company of the rications in the	Corp.	ill for 1/24/37