

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-08986
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	South Eunice Unit
8. Well No.	20
9. Pool name or Wildcat	Eunice 7Rvrs Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER Injection	2. Name of Operator CONOCO INC.
3. Address of Operator 10 Desta Drive W. Midland, TX 79705	4. Well Location Unit Letter I :1980 Feet From The South Line and 660 Feet From The East Line Section 21 Township 22S Range 36E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Squeeze Liner ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-9-90 Blew well down to pit. POOH w/pkr & tbq. Run csg scraper to 3630'. Pumped 35 bbls water to est circ. Spot 18 sx sand down tbq. WOS 1 hr. Tagged TOS @ 3708'. Pumped 2 sx sand. Wait 1 hr. Tagged @ 3693'. Spot 3 sx sand. Tagged @ 3683'. Dump 1 sx sand. SDON. Tagged TOS @ 3683'. Dump 1 sx sand. WOS 30 min. TOS @ 3675'. Spot 1 1/2 sx Cal-Seal 3668'-3675'. Set cmt rtnr @ 3590'. Pump through rtnr. Squeeze liner shoe 3660'-3670' w/ 150 sx Class H w/2% KCL, 0.5% CaCl2, & 1% Halad 332. Squeezed to 1750#. Left 1/2 sx cmt on top of rtnr. Tag TOC @ 3518'. Est circ. DO cmt 68'. Hit cmt rtnr 3586'. DO part of rtnr 3588'. Reverse out clean. Est circ. DO rest of cmt rtnr. DO cmt to 3668'. Circ clean. Pressure test csg shoe. Pressure bled off. Run csg scraper to 3621'. Isolate leak. DO & CO 3668'-3804'. Circ hole. Circ pkr fluid down backside. Set pkr @ 3643'. Pressure test csg to 500# for 15 min. Held.

NMOCD (3) File

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ceal O. Yarbrough TITLE Sr Analyst--Gas Prod DATE 10-08-1990
TYPE OR PRINT NAME Ceal O. Yarbrough TELEPHONE NO. 9156865583

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: