

Dec. 1973

N. M. OIL & GAS COMMISSION UNITED STATES  
 P. O. BOX 1807 DEPARTMENT OF THE INTERIOR  
 NORTH NEW MEXICO GEOLOGICAL SURVEY

Form Approved.  
 Budget Bureau No. 42-R1424

# SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ **Water Inj**
2. NAME OF OPERATOR **CONOCO INC.**
3. ADDRESS OF OPERATOR **P. O. Box 460, Hobbs, N.M. 88240**
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
 AT SURFACE: **660' FSL + 660' FWL**  
 AT TOP PROD. INTERVAL:  
 AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
 FRACTURE TREAT ☐  
 SHOOT OR ACIDIZE ☐  
 REPAIR WELL ☐  
 PULL OR ALTER CASING ☐  
 MULTIPLE COMPLETE ☐  
 CHANGE ZONES ☐  
 ABANDON\* ☐  
 (other) **Clean Out** ☒

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

**MIRU. Rel pkr. Tag @ 3583'. CO to 3823'. Set pkr**  
**Acidize w/ 11.9 BBLs of 15% HCL-NE-FE. Flush**  
**w/ 30 BBLs 9#. Pump in at 500 psi. Place well on**  
**injection. Inj 320 BWPD @ 640 psi on 8-18-84.**

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Wm A. Harkins* TITLE Administrative Supervisor DATE 10/17/84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY *[Signature]* TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 CONDITIONS OF APPROVAL IF ANY \_\_\_\_\_

OCT 25 1984

*Carlsbad,* NEW MEXICO

\*See Instructions on Reverse Side