

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other. INJECTION

2. Name of Operator
Conoco Inc.

3. Address and Telephone No.
10 Desta Drive STE 100W, Midland, TX 79705 (915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660' FSL & 1980' FEL, SEC. 22, T-22S, R-36E, UNIT LTR 'O'

5. Lease Designation and Serial No.
LC 030133B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
S. EUNICE UNIT #26

9. API Well No.
30-025-08993

10. Field and Pool, or Exploratory Area
EUNICE 7 RVRS QUEEN SO.

11. County or Parish, State
LEA, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other INSTALL LINER	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-8-91 MIRU. RIH W/ BIT & SCRAPER TAG @ 3713' - POOH. RIH W/ BAILER CLEAN OUT TO 3640' POOH. RIH W/ DUMP BAILER-DUMP 1/2 SX CAL SEAL PLUG - POOH.
GIH W/ 3 1/2" FIBERGLASS CASING LINER- SET AT 3645' (TOP AT 3182').
PUMP 100 SX CLASS C CMT-SET LINER HANGER SQUEEZE W/ 470 SX CLASS C CMT.
RIH W/ 2 3/4" BIT, DRILL OUT TO 3771' CIRC HOLE CLEAN.
GIH W/ SEAL NIPPLE AT 3643' & LATCH INTO PACKER AT 3186', PRESS CSG TO 500 PSI FOR 30 MIN
RDMO
WELL RETURNED TO INJECTION 8-1-91

14. I hereby certify that the foregoing is true and correct

Signed [Signature]
(This space for Federal or State office use)

Title SR. REGULATORY SPEC.

Date 6-17-92

Approved by _____
Conditions of approval, if any:

Title

Date