

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other INJECTION
2. NAME OF OPERATOR
CONTINENTAL OIL Co.
3. ADDRESS OF OPERATOR
P.O. BOX 460 Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660/S + 1780/E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☒REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

RECEIVED

JUN 19 1979
(NOTE: Report results of multiple completion or zone change on Form 9-330.)U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to clean out, repair, and acidize the subject well to improve injection as follows:

MIRU, C.D. to ± 3780'

PERF @ 3656 - 60, 3809 - 82, 3692 - 3700, 3712 - 20, 3759 - 616 w/ 115 PSI

disp. annulus w/ pkr fluid.

acidize w/ 1470 gallons 15% HCl-H₂O acid, divert w/ 900' rock salt & 200 gallons BRINE water.

follow w/ 2010 gallons 15% HCl-H₂O acid. flush w/ 25 bbls TFW.

run inj. sept., resume inj.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm. A. ButterfieldTITLE Admin. Supl.DATE 6-18-79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

USGS 5

Partners 21

FILE

*See Instructions on Reverse Side

APPROVED
JUN 19 1979
ACTING DISTRICT ENGINEER