

(SUBMIT IN TRIPLICATE)

Land C	ffice La	s Cr	ces
Lease N	lo. LC	0301	.33 b

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		5	
Unit	nmpu		

NOTICE OF INTENTION TO DRILL	ND REPORTS ON WELLS
TOTAL OF INTENTION TO CHANGE PLANS	THE TOP OF WATER SHUT-OFF
THER TION TO TEST WATER SHITT-OFF	REPORT OF SHOOTING OR ACIDIZING
THE PROPERTY OF THE PROPERTY O	REPORT OF ALTERING CASING
THE OF INTENTION TO SHOOT OF ACIDITE	REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALTER CASING	REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ABANDON WELL	HELL HISTORY
(INDICATE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER DATA)
Meyer R-22	
	July 30 , 1956
Well No. 9 is located 660 ft. from	ine and 1080 to the second
(1/2 Bec. and Sec. No.)	Arthur wester
Granty or Su (County or Su (County or Su	(Mer dian)
(Field) (County or Su	abdivision)
tate names of and expected depths to objective sands; show sizes, we	OF WORK
It is intended to drill this bove location to an approximate seemented in accordance with U.S.G. quirements will be complied with	eights, and lengths of proposed casings; indicate mudding jobs, cement-important proposed work) Well with rotary tools at the
It is intended to drill this bove location to an approximate mented in accordance with U.S.G. quirements will be complied with The following casing pattern o' with 350 sacks, coment to be casing set at 3825' with 1100 sately 1200'.	well with rotary tools at the TD of 3825'. Casing will be .3. standards and other special h. is planned: 8 5/8" OD set at circulated to surface, 5 1/2" cacks, cement to return to approx-
It is intended to drill this bove location to an approximate mented in accordance with U.S.G. quirements will be complied with	well with rotary tools at the TD of 3825'. Casing will be .5. standards and other special h. is planned: 8 5/8" OD set at circulated to surface, 5 1/2" Packs, cement to return to approx-
It is intended to drill this bove location to an approximate mented in accordance with U.S.G. quirements will be complied with The following casing pattern of with 350 sacks, cement to be casing set at 3825' with 1100 sately 1200'. understand that this plan of work must receive approval in writing mpany Continental Cil Company	well with rotary tools at the TD of 3825'. Casing will be .3. standards and other special h. is planned: 8 5/8" OD set at circulated to surface, 5 1/2" cacks, cement to return to approx-