

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ INJECTION  
2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY  
3. ADDRESS OF OPERATOR  
P.O. Box 460 Hobbs, N.M. 88240  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980/5 660  
AT TOP PROD. INTERVAL: 1980/5  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☒  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED

JUN 19 1979

(NOTE: Report results of multiple completion or zone  
U. S. GEOLOGICAL SURVEY Form 9-330)  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to clean out, acidize, and perf the subject well to ripe and injection.

- MRL, and C.O. to  $\approx$  3780.

- PERF @ 3652-6, 3675-80, 3691-3700, 3714-9, 3732-40, 3760-4 w/ 150PA.

- displ annulus w/ perf fluid.

- pump 1512 gallon of 15% HCl-H<sub>2</sub>O acid thru ports, diverting rock salt & brine into.

Follow w/ 2016 gallons of 15% HCl-H<sub>2</sub>O acid. RUN prod. ceph. Resume injection

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Area Super DATE 6-18-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

USGS 5

PTMRS. 2.1

FILE

\*See Instructions on Reverse Side

