For (I	m 9- leb. 19	831 a 951)		
				ş

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office		Crt	100	\$
		030	133	b
Ti-is	14. A	rt.		

TICE OF INTENTION TO ABANDON	LANSER SHUT-OFFOR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING
(INDICA	TE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)
yer 3-22		October 15 , 19
No. 12 is loca	ted <u>560</u> ft. from.	$\begin{cases} E \\ S \end{cases} \text{ line and } \begin{cases} 660 \\ \text{ft. from } \\ 1000 \\ \text{ft. from } \end{cases} \text{ line of sec. } \frac{22}{1000}$
(1/2 Sec. and Sec. No.)	(Twp.)	Range) (Meridian)
(Field)	(County or	Subdivision) (State or Territory)
	DETAI	LS OF WORK
e names of and expected depths t	DETAIl to objective sands; show size ing points, and all of	LS OF WORK ps, weights, and lengths of proposed casings; indicate mudding jobs, cemther important proposed work)
spadded 4:00 marks with 350 sacks mg with 300% be man 117 joints remant 600'. Fl after drilling	DETAIL to objective sands; show size ing points, and all of 29-27-56. Cament circ fore and after 5 1/2° Gasin ug down 10-11 plug.	LS OF WORK sa, weights, and lengths of proposed casings; indicate mudding jobs, cem ther important proposed work) an 11 joints 5/8" casing set at glated. Flux down 7-26-56. Test a drilling plug. Tested 12. Sat at 1600 with 1100 sacks. 16 So Tested Casing with 800 before operations may be commenced
padded 4:00 mith 350 sacks with 350 sacks with 300 be sand that 117 joints contact 600 . It after drilling	DETAIL to objective sands; show size ing points, and all of 29-27-56. Cament circ fore and after 5 1/2° Gasin ug down 10-11 plug.	LS OF WORK sa, weights, and lengths of proposed casings; indicate mudding jobs, cem ther important proposed work) an 11 joints 5/8" casing set at glated. Flux down 7-26-56. Test a drilling plug. Tested 12. Sat at 1600 with 1100 sacks. 16 So Tested Casing with 800 before operations may be commenced
predict 4:00 makes the with 350 sacks in with 350 sacks in with 500 be an 117 joints consect 600 . Fi	DETAIL to objective sands; show size ing points, and all of 29-27-56. Cament circ fore and after 5 1/2° Gasin ug down 10-11 plug.	LS OF WORK sa, weights, and lengths of proposed casings; indicate mudding jobs, cem ther important proposed work) an 11 joints 5/8" casing set at glated. Flux down 7-26-56. Test a drilling plug. Tested 12. Sat at 1600 with 1100 sacks. 16 So Tested Casing with 800 before operations may be commenced