

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Sun Oil Company	8. Farm or Lease Name Peerless et al Com
3. Address of Operator P.O. Box 1861, Midland, TX 79702	9. Well No. 1
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 22-S RANGE 36-E N.M.P.M.	10. Field and Pool, or Wildcat Jalmat Yates
11. Elevation (Show whether DF, RT, GR, etc.) 3537 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☒ Foam frac & acidize

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Kill well. MIRU, load hole w/15 bbls 5% KCL wtr/lower pkr thru perfs/ran Permalach pkr on 2 7/8 tbg to 3268 thru to 3480/Spot 300 gals acid 3480-3302, raise pkr to 3237. Western & Nowsco acdz perfs 3350-3478 w/2000 gals 50 quality 15% NEfehcl in 2 stages using 300 lbs. GRS BJ frac Yates Perfs - 3350-3478 w/40,000 gal 5% KCL foamed to 70 quality w/nitrogen carrying 48,000# in 2 eq stages diverted w/400# GRS & 100# BAF in 500 gal foam saturated brine. Flush w/foamed 5% KCL block action 3050-3450 Swab 1 1/2 hrs well kicked off flow 2 1/2 hours. Wash SD out tbg w/10 bbls 5% KCL. Otis WL run 1 1/2 sinker bar. Tag fill 3477, run & set 2" type SN plug in Ostsd 3232, rlse. OSTSD POH LD 2 7/8 tbg reran 2 3/8 tbg w/OSTSD shuck to 3200 circ pkr fluid latch Ostsd 3232 w/8000# compression remove BOP install well HD, test csg Otis ret SN plug test. POH w/Permalach pkr ran 2 3/8 tbg with pump & rods.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dee Ann Kemp TITLE Accounting Assistant I DATE 7-23-81

APPROVED BY [Signature] TITLE [Signature] DATE JUL 27 1981

CONDITIONS OF APPROVAL, 31 MAY: