

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FNL + 1700' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☒

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

LC-031620 (B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

SKAGGS B

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

GLORIETA / BLINERY / DRINKARD

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 12, T-20S, R-37E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

(AS REQUESTED BY NMOCO-HOBBS)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SEE ATTACHED PROCEDURE.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Butterfield TITLE Administrative Supervisor DATE 6/28/83

APPROVED PETER W. CHESTER (This space for Federal or State office use)
APPROVED BY Sgt. TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUL 11 1983

SURFACE WATERFLOW REPAIRRECOMMENDED PROCEDURE:

1. MIRU.
2. SI well, open the Bradenhead valve and relieve the surface-production casing annulus pressure.
3. Connect the Bradenhead to a pump truck w/reliable pressure gauge, and connect another gauge to the tubing casing annulus.
4. Make several attempts to pump 10 Bbls fresh water between the surface - production casings at 800 psi maximum pressure, and report injection rate and pressure and any pressure increase in the tubing-casing annulus to the area engineer.
5. If fresh water is pumped between the casings at 800 psi or less, POOH w/rods and pump, and run tracer survey to determine how deep the fresh water will reach behind the production casing. Contact Engineering.
6. If fresh water could not be pumped between the surface and production casings at 800 psi or less, the POOH w/rods and pump, install BOP, tag for fill with tubing, and POOH.
 - A. GIH w/7" casing scraper on workstring, and circulate well clean w/fresh water treated w/2% KCl and 1:1000 Adomall to 6950' and POOH. If circulation cannot be obtained, run scraper to 3000' and POOH.
 - B. GIH w/7" csg packer on workstring, set packer @ 2800', load back-side w/TFW, and pressure the tubing-casing annulus w/500 psi. Run Bradenhead tracer survey at 1000 psi maximum injection pressure. If fluid does not go past the casing shoe, contact Engineering. Rig down, move off. Remedial work is being planned at this time.
7. Rig up and cement between the surface and the production casings at 1000 psi maximum pressure and 1 BPM if packer is used. If packer is not used, the maximum pressure is 800 psi and the injection rate is not to exceed that of the fresh water rate pumped between the casings prior to cementing.

NOTE: This step only if tracer survey shows water is going past casing shoe.

Cement required to cement to 1434'

Between casings: 0.2009 cu. ft./ft: 239 sacks, plus 20 sacks

Lead-in with 20 sacks Class "C" cement w/18% salt mixed with 6.3 gals. fresh water/sack.

Tail-in with 239 sx. Class "C" cement w/2% CaCl_2 mixed w/6.3 gals. fresh water/sack, and slurry weights 14.8 lbs/gal

Pressure and rate should be recorded during cementing and sent to the Division Office.
8. Displace cement slurry w/fresh water through the wellhead. Do not displace cement in the casings annulus. Close the Bradenhead valve. SION.
9. Unseat packer, and POOH w/workstring and packer, only if used.
10. Run production equipment, and rig down.
11. Put well on production and report results to the Division Office.

RECEIVED

JUL 12 1983

O.C.D.
HOBBS OFFICE