

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Amoco Production Company</i>		8. FARM OR LEASE NAME <i>Hillbilly "B" Federal</i>
3. ADDRESS OF OPERATOR <i>P.O. Box 68, Hobbs NM 88240</i>		9. WELL NO. <i>10</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <i>660' FNL X 1980' FEL NW/4 NE/4 Unit B</i>		10. FIELD AND POOL, OR WILDCAT <i>Wheir Blinberry</i>
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>22-20-37</i>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3549' RDB</i>		12. COUNTY OR PARISH <i>Lea</i>
		13. STATE <i>NM</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

☐
☐
☐
☐
☐

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

☐
☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

☐
☐
☐
☐

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

☐
☐
☐
☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MISU 2-14-85 and POH with production equipment. Ran 4 1/2" CIBT, set at 6400' and cased with 35' cmt. Perforated 5780-74, 70-62, 44-40, 26-26, 18-14, 11-07, 5704-5698, 90-79, and 76-70 with a 3 1/8" csg gun, 4SPF. RIH with PPI ppr and acidized perfs 5670-5780' with 3300 gals 15% HCl. Swabbed back load. Frac down tbg with 669 bbls 40% x-linked gelled 2% HCl, 60000 lbs 20/40 sand. Flow tested and swab tested. Cleaned out sand to 6360' and circulated clean. Hot oiled tbg to remove paraffin. Ran production equipment, seating nipple at 5806'. Tested pump to 500 psi, tested OK. MOSU 3-5-85 and began pump testing. Last 24 hrs pumped 31 BO, 45 BLW, and 1 MCF. Well is currently producing.

0-5 BLM/C 1-JRB 1-FJN 1-GCC

18. I hereby certify that the foregoing is true and correct

SIGNED

Larry C. Clark

TITLE

Asst. Admin. Analyst

DATE

3-15-85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Mike
MAR 22 1985

*See Instructions on Reverse Side

M

RECEIVED

MAR 25 1985

6-12-85
FBI - NEW YORK