

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-B1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ <u>Dual</u>		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <u>Continental Oil Company</u>		8. FARM OR LEASE NAME <u>SEMS Blinbry Tubb</u>
3. ADDRESS OF OPERATOR <u>P. O. Box 460, Hobbs, New Mexico 88240</u>		9. WELL NO. <u>82</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) <u>At surface</u> <u>1650' FWL & 660' FEL, Sec. 15-20-37, Lea County, New Mexico.</u>		10. FIELD AND POOL, OR WILDCAT <u>Monument Tubb and Weir Blinbry Pools</u>
14. PERMIT NO.		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 15, T. 20S. R-37E</u>
15. ELEVATIONS (Show whether DF, ST, GR, etc.) <u>3578' D.F.</u>		12. COUNTY OR PARISH <u>Lea</u>
		13. STATE <u>N.M.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETS ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Squeeze & Abandon Blinbry</u> ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

BEFORE: T.D. 6700', PB 6695', RBM 10' AGL. Elev. 3568'. 5 1/2" csg. set @ 6700'. Perfs. 5816, 5829, 5831, 5841, 5850, & 5853' W/1 JSPF. Dual completed in Tubb & Blinbry. Perfs. 6487 & 6490' W/2 JSPF and 6528, 6532, 6557, 6569, 6571, 6574, 6581' W/1 JSPF. Prod. 54 BO, 3 BW & 217 MCFG. Allow. 37 B.O.

WORK DONE: Squeezed Blinbry perfs 5826-5853' w/100 sacks cement. Rev. out 60 sx. Drilled out cement 5700-5853'. Pulled plug from Model "D" pkr. Pushed pkr. to 6690'. Ran tubing, set @ 6690'. S.N. @ 6576'.

AFTER WORKOVER: T.D. 6700', P.B. 6690', R.B.M. 10' AGL. Elev. 3568'. 5 1/2" csg. set @ 6700'. No change in Tubb zone. Tested 4-19-67. Tubb flowed 94 B.O., 8 B.W, w/165 MCFG in 24 hrs. T.P. 200#. C. # 46/64" choke. GOR 1755. Allow. 94. Workover started 3-9-67. Completed 3-17-67.

APPROVED

MAY 19 1967

J. L. GORDON
ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED

James R. Smith

TITLE Supervising Engineer

DATE

5-19-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

USGS-5 ATL-Ros-2

PAN AM-Hobbs-2

CHEV-Mid-2

FILE