Form 9-331 (May 1963)		I'~CD STATES I OF THE IN	TEDIOD	(Other instructions	re- 5. L	EASE DESIGNATION	eau No. 42-R
		OLOGICAL SURV		(6200 22-27)	I	c 031621	(b)
SU (Do not use t	INDRIV NOTICE	C AND DEDO	DTC ON	WELLS to a different reservoir.	6. n	F INDIAN, ALLOTT	ED OR TRIBE
1.	994 <b>L</b> S (	- 03 - 1250			7. 0	UNIT AGREEMENT I	NAME
OIL X GAS WEL		1 09 04	· · · · · · · · ·	+ 3 13 <b>5</b> 4	8. E	SEMU FARM OB LEASE N.	AME
2. NAME OF OPERATOR		anu		# 3 1명 <b>8</b> 4		EMU Bline	bry-Tu
3. ADDRESS OF OPERA				- A	1 -	WELL NO.	
Box 460,	Hobbs New	Mexico	with any Stat	e requirements.*	8 NtMi	rurrieid.	OR WILDCAT
See also space 17 At surface  1650! FNL	. & 660' FEL	of Sec. 15			Mo	n Tubb & SEC., T., E., M., O. SURVEY OR AR	Weir B
Lea Count	y, New Mexi	co, NMPM.				15-20-37	
14. PERMIT NO.		15. ELEVATIONS (Show w	vhether DF, RT,	gr, etc.)		COUNTY OR PARI	
		3578 DF				Lea	N.M.
16.	Check Appl	ropriate Box To Ind	dicate Natu	re of Notice, Report,	or Other	r Data	
	NOTICE OF INTENTIO			SUL	BSEQUENT	REPORT OF:	· ·
TEST WATER SH	UT-OFF PU	LL OR ALTER CASING		WATER SHUT-OFF	<u>X</u>	REPAIRIN	
FRACTURE TREAT	1   ,,,,	LTIPLE COMPLETE	_	FRACTURE TREATMENT		ALTERING	
SHOOT OR ACIDIZ	" <del>"</del>  ——	ANDON*		8HOOTING OR ACIDIZING (Other)		1 1 3	
REPAIR WELL	CB	ANGE PDAMS		(Nore: Report re	sults of p	nultiple complete n Report and Log	101141./
nent to uns we	31 B-1			etails, and give pertinent of s and measured and true v	lates, incl ertical de	uding estimated pths for all mar	date of starti kers and zone
Drilled sx clas: W/4% ge	31 B-1	0-6-64. Set t W/8% gel a wn at 2:45 a vey. W.O.C		Completion or Received and give pertinent of and measured and true versions at 6 sx class "C" 3-64. Top of rs. Tested wi	lates, incl ertical de	W/600 ent nt at 260	date of starti kers and zone
Drilled sx clas W/4% ge by temp for 30	to 6700' 10s "C" cement  1. Plug doverature surm  min. Tester	o-6-64. Set t W/8% gel a wn at 2:45 a vey. W.O.C d O.K.	t 5 1/2 and 100 am 10-8 . 36 hr	etails, and give pertinent of s and measured and true v	7001 cemer cemer th 10	w/600 at 260 and a separate of the first service of	date of startikers and zone
Drilled sx clas W/4% ge by temp for 30	to 6700' 10s "C" cement 1. Plug down erature sur min. Teste	o-6-64. Set t W/8% gel a wn at 2:45 a vey. W.O.C d O.K.	t 5 1/2 and 100 am 10-8 . 36 hr	etails, and give pertinent of and measured and true versions at 6 sx class "C" 6-64. Top of rs. Tested wi	7001 cemer cemer th 10	w/600 at 260 and a separate of the first service of	date of startic kers and zone that so the control of all the sound to the control of the control

\*See Instructions on Reverse Side

J. L. GOLDA A

ACHNO DISTRICT SYSTEM I