

Form 9-581a
(Feb. 1961)

APPROVED

(SUBMIT IN TRIPLICATE)

HOBBS OFFICE O. C. C.

JUN 12 1964

UNITED STATES

DEPARTMENT OF THE INTERIOR

J. L. GORDON

GEOLOGICAL SURVEY

ACTING DISTRICT ENGINEER

Land Office New MexicoLease No. NM-04405Unit P

JUN 11 1964

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Bass-Federal

June 10, 1964

Well No. 1 is located 660 ft. from [S] line and 660 ft. from [E] line of sec. 19SE/4 SE/4 Sec. 19 22-S 32-E NMPM

(1/4 Sec. and 1/4 Sec. No.)

(Twp.)

(Range)

(Meridian)

Wildcat

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3610 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well drilled to TD of 4802' No shows of oil or Gas encountered. We will plug according to instructions of U.S.G.S.
Cement Plugs to be set as follows: 4600'-4700', 3700'-3300', 900'-1000', 425'-525'. Top to 100'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Ralph LoweAddress Box 832Midland, TexasBy [Signature]Title agent