

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-031736(B)	
2. NAME OF OPERATOR Pan American Petroleum Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 68, Hobbs, New Mexico		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL x 1980 FWL Sec. 22 (Unit F, SE 1/4 NW 1/4)		8. FARM OR LEASE NAME O.J. GILLULLY "B"	
14. PERMIT NO.		9. WELL NO. 11	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3549' R.D.B.		10. FIELD AND POOL, OR WILDCAT WEIR BLINERY	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 22-20-37 NMPM	
		12. COUNTY OR PARISH LEA	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☒
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In an effort to increase productivity, remedial work proposed as follows:

Perforate Blinery at intervals 5684, 5712, 5741, 5752 and 5759' w/ 1.5 SPF. Set cast iron plug at approx. 5800. Wash + soak perfs w/ 2000 gallons acid. Frac w/ 40,000 gal gel brine, 1/2 to 1 1/2" sand/gal, + 4000 # glass beads. Evaluate and restore to production.

TD-6829'

5 1/2" CSA 6829

PBD-6240' (CTAPW/10' OM) PERFS. 5694, 5725, 5768, 5812, 5856, 5907, 5934, 5963.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supr

DATE

4-18-66

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

APR 21 1966

A. T. DOWD
DISTRICT ENGINEER

*See Instructions on Reverse Side

0-4- USGS-H
1-JWB
1-SUP
1-RRY