

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103 -
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator TEXACO INC. 3. Address of Operator P. O. BOX 728, HOBBS, NEW MEXICO 88240 4. Location of Well UNIT LETTER F 2310 FEET FROM THE WEST LINE AND 2080 FEET FROM THE NORTH LINE, SECTION 13 TOWNSHIP 20-S RANGE 37-E NMPM. 15. Elevation (Show whether DF, RT, CR, etc.) 3562' (DF)	7. Unit Agreement Name 8. Farm or Lease Name L. R. KERSHAW 9. Well No. 10 10. Field and Pool, or Wildcat DEER TUBB EAST 12. County LEA
---	---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER REPAIR WATER FLOW <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. RIG UP. PULL RODS AND PUMP. INSTALL BOP. PULL TUBING.
2. LOG TUBB STRING. SET CIBP IN TUBB STRING @ 4500' AND SPOT 40' CEMENT ON PLUG.
3. SET CIBP IN DRINKARD STRING @ 4500' AND SPOT 40' OF CEMENT ON PLUG.
4. PERFORATE TUBB STRING W/ 2-JS @ 1469'.
5. CEMENT TO SURFACE THROUGH 2 7/8" CASING PERFORATIONS @ 1469' W/ 600 SX. CLASS H CEMENT CONTAINING 2% CACL. SQUEEZE W/ ADDL. 200 SX. CLASS H CEMENT CONTAINING 2% CACL. WOC. DOC. TEST.
6. DRILL OUT CIBP IN BOTH STRINGS. INSTALL PUMPING EQUIPMENT. TEST AND RETURN TO PRODUCTION.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE ASST DIST MGR DATE 8-19-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE AUG 22 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

AUG 19 1993

O.C.D.
HOBBS OFFICE