

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ For ☒
5. State Oil & Gas Lease No.

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - M (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name ---
2. Name of Operator Texaco Inc.	8. Farm or Lease Name M.B. Weir "B"
3. Address of Operator P.O. Box 728, Hobbs, NM 88240	9. Well No. 9
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 2180 FEET FROM East LINE, SECTION 12 TOWNSHIP 20-S RANGE 37-E NMPM.	10. Field and Group, if known Skaggs Glorieta, Skaggs Drinkard, Weir Blinebry East.
11. Elevation (Show whether DF, RT, GR, etc.) 3565' (DF)	12. County Lea


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
CHANGE PLANS ☐	OTHER ☐
OTHER ☒ Open & treat Glorieta, addl. pfs. & treat Drinkard, Tiple Downhole Commingle.	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

1. Rig up. Pull rods & pump from Drinkard Zone. Pull tubing.
2. Perforate Drinkard 2-7/8" csg string w/2-JSPF @ 6646', 53', 76', 83', 90', 6710', 25', 33', 38', 57', 6860', 66', 73', & 6886'.
3. Set RBP in Blinebry string @ 5600'.
4. Set pkr in Drinkard string @ 6600'. Frac Drinkard perfs. 6646-6886' w/36,000 gal. cross linked gel carrying 9000# 100 mesh sand & 36,000# 20/40 sand in 3 stages.
5. Perforate 2-7/8" Blinebry string w/2-JSPF @ 5270', 74', 84', 5313', 18', 33', 41', & 5345'.
6. Set pkr @ approx 5220'. Acid frac Glorieta perfs 5270-5345' w/8000 gal gelled acid, 10,000# 100 mesh sand & 10,500# 20/40 sand. Flush.
7. Pull RBP's, install pumping equipment & test as triple down-hole commingle, Glorieta, Drinkard & Blinebry, NMOC order #R-6113, Case 6628.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  TITLE Asst. Dist. Supt. DATE 7-3-80

APPROVED BY Jerry Sexton TITLE Asst. Dist. Supt. DATE JUL 11 1980

CONDITIONS OF APPROVAL, IF ANY: