

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-025-20964

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

NM 879910

7. Lease Name or Unit Agreement Name:

C.H. Weir "A"

8. Well No.

10

9. Pool name or Wildcat

Weir, Blinbry, East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Texaco Exploration & Production, Inc.

3. Address of Operator

P. O. Box 3109, Midland, Texas 79705

4. Well Location

Unit Letter J : 1980 feet from the South line and 2306 feet from the East line

Section 12

Township 20S Range 37E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- Set 2 7/8" CIBP Z-Side @ 5700' (Skaggs-Drinkard) Fill 2 7/8" Csg w/140 Sx plug 5700'-Surf
- Set 2 7/8" CIBP Y-Side @ 5700' (Weir) Fill 2 7/8" Csg w/75 Sx plug 5700'-2700' WOC Tag
- Perf 6 holes Y-Side @ 2700', Sqz 50 Sx plug 2700'-2500' (T-Salt)
*Ensure TOC Calc behind 2 7/8" @ 2331' WOC - Tag
- Fill 2 7/8" Csg w/65 Sx plug 2500'-Surf (8 5/8" Shoe T-Salt)
- Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE James T. Corbitt TITLE FACILITY ENGINEER DATE 3/19/01
Type or print name JAMES T. CORBITT Telephone No 915-688-4438
(This space for State use)

APPROVED BY _____ TITLE _____ DATE MAR 21 2001
Conditions of approval, if any: _____

(1 STRING CSNG)

OPERATOR TEXACO Exploration & Production
LEASENAME C. H. WEIR "A"

SECT 12 TWN 205 RNG 37E
FROM 1980 NSL 2306 EWL
TD: 6850 FORMATION @ TD WEIR
PBDT: 5977 FORMATION @ PBDT BLINERBY

	SIZE	SET @	TOC	TOC DETERMINED BY	
SURFACE	85/8	1419	SURE	CIRC	
INTMED 1	27/8	6842	2331	CALC	
INTMED 2					
PROD	27/8	6847	2331	CALC	
	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					
	CUT & PULL @			TOP - BOTTOM	
INTMED 1			PERFS	5768 - 5976	
INTMED 2			OPENHOLE	-	
PROD					

*** REQUIRED PLUGS DISTRICT I**

RUSTLER (ANHYD)	
YATES	
QUEEN	
GRAYBURG	
SAN ANDRES	
CAPTAN REEF	
DELAWARE	
BELL CANYON	
CHERRY CANYON	
BRUSEY CANYON	
BONE SPRING	
GLORIETA	
BLINEBERRY	
TUBB	
DRINKARD	
ABO	
WC	
PENN	
STRAWN	
ATOKA	
MORROW	
MISS	
DEVONIAN	

[illegible]

8/83 PEF
@1469 CIRC
CMT TO SUEF

85/8
@ 1419
TOC SURF

PERF @ 2700

5768-5976
Communicated

 $2\frac{7}{8}$

© 6842-6847
Toc 2331

TD 6850

6676⁷
6839 :

Z-side (Skages-Deinhard)

Y-Side (weie)