

L CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Texaco Inc.	8. Farm or Lease Name E.H.B. Phillips "C"
3. Address of Operator P. O. Box 728, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 10 TOWNSHIP 20-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Eumont Y-7R-Q
15. Elevation (Show whether DF, RT, GR, etc.) 3622' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- MIRUPU. Install BOP. TIH w/2-1/16" workstring, then spot 100' cmt. plug (3 sxs.) @ 4975-5075'. TOH.
- TIH w/free point tool. Determine top of 2-7/8" cmt. (est. @ 3550').
- Cut 2-7/8" csg. above cmt. top w/chemical cutter.
- TOH w/2-7/8" csg.
- TIH w/workstring to csg. stub. Lower workstring 50' into csg., then spot 100' cmt. plug (22 sxs.) across stub.
- Raise workstring to 2800'. Spot 100' cmt. plug (38 sxs.) @ 2700-2800', across base of salt.
- Raise workstring to 1450'. Spot 200' cmt. plug (67 sxs.) @ 1250-1450', across top of anhydrite @ 1400' and 8-5/8" csg. shoe @ 1289'.
- Raise workstring to 50'. Spot 50' cmt. plug (16 sxs.) @ 0-50'. TOH.
- Install dry hole marker. RDPU. Clean location.

THE COMPLETION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief. 397-3571

SIGNED J. A. Hobbbs TITLE Hobbs Area Superintendent DATE AUG 16 '88
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
PROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: