

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
NONE

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	NONE
3. Address of Operator	8. Farm or Lease Name
TRWACO Inc.	C. H. Weir "B"
4. Location of Well	9. Well No.
UNIT CENTER P 660 FEET FROM THE South 660 FEET FROM	6
THE East LINE, SECTION 11 TOWNSHIP 20-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat
	Glorieta & Drinkard
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3574' (D. F.)	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 6900'  
8 5/8" O. D. Casing Cemented at 1411'

Glorieta Zone: Ran 6886' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, And cemented at 6896', RA collar & 2' sub at 5720'. Plug at 6865'.

Drinkard Zone: Ran 6890' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, And cemented at 6900', Plug at 6890'.

Cement above strings with 400 Sx. Class "C" 8% gel with FRA, plus 400 Sx. Class "C" 4% gel. Pump plugs down with 500 gals acetic acid. Tested with 2000 P. S. I. for 30 minutes from 5:30 P. M. to 6:00 P. M. January 28, 1965. Tested O. K. Job complete 6:00 P. M. January 28, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. D. Raymond</u>	TITLE Assistant District Superintendent	DATE February 2, 1965.
APPROVED BY <u>[Signature]</u>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY		