

COUNTY	LEA	FIELD	Monument-Tubb	STATE	NM
OPR	CONTINENTAL OIL COMPANY				MAP
	24 Britt "E"				
	Sec. 11, T-20-S, R-37-E				CO-ORD
	1980' fr S Line & 660' fr W Line of Sec.				
	Spd 5-11-65				CLASS
	Cmp 6-8-65				E
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG:	Yates	2704		
		Queen	3513		
7 5/8" 1344' 470		Glor	5263		
4 1/2" 7000' 600		Bli	5843		
		Tubb	6379		
		Drkd	6711		
LOGS EL GR RA IND HC A					
		TD 7000'			

IP Tubb Perfs 6494-6696' Flwd 180 BOPD + 26 BW. Pot. Based on 18½ hr test of 139 EO + 20 BW thru 18/64" chks., IP 250#, gravity 39., GOR 2528.

Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.		
CONT. Roy H. Smith	PROP DEPTH 6725'	TYPE
DATE		

F.R. 5-13-65
 PD 6725' - Tubb
 Contractor - Roy H. Smith
 5-17-65 Drlg. 4008'.
 5-24-65 Drlg. 5915'.
 6-1-65 TD 6520', on DST.
 Cored 6483-6520', rec 37' being:
 33½' dolc., w/sli to good show, bldg oil & gas;
 3½' sd., bldg oil & gas.
 6-7-65 TD 7000', tstg.
 DST 6488-6520', open 3½ hrs,
 GIS 5 mins, OIS 40 mins,
 Flwd 7 EO in 2 hrs 50 mins,
 Circulated out 44 EO,
 30 min ISIP 2485#, FP 337-1840#,
 ESIP 2421#.

6-7-65

Continued

Cored 6520-72', rec 52' being:

41' dolo., w/sli to good show & poro;

4' siltstone, w/NS; 7' sd., w/NS.

Cored 6572-6624', rec 52' dolo., w/4' porosity.

Cored 6624-6675', rec 51' being:

2' lm., w/fair vuggy poro; $\frac{1}{2}$ ' lm., w/PPP;

9' dns lm; $\frac{1}{2}$ ' sh; 13' dolo., w/scatt PPP;

26' dns dolo.

Perf (Tubb) @ 6494', 6496', 6498', 6506',

6570', 6584', 6592', 6596', 6601', 6613',

6686', 6696' W/1 SPI

Ac. 5000 gals.,

Flwd 134 BNO + 37 BLW in 8 hrs thru 28/64"

& 10/64" chks.

6-14-65 TD 7000', COMPLETED.